



Connect more with less  
HelaCon Plus Mini – Now 40% smaller\*



- 40% smaller – space saving design
- Low insertion force – easy to use
- Round-shaped wire insertion port
- Easy access voltage test entry

\*The new HelaCon Plus Mini is up to 40% smaller than the standard HelaCon Plus connectors.

**HellermannTyton**

HellermannTyton Ltd  
Wharf Approach  
Aldridge, Walsall, West Midlands  
WS9 8BX  
Tel.: +44 1922 458 151  
Fax: +44 1922 743 053  
Email: [info@HellermannTyton.co.uk](mailto:info@HellermannTyton.co.uk)  
[www.HellermannTyton.co.uk](http://www.HellermannTyton.co.uk)





### Connectors

#### HelaCon Plus Mini


HelaCon connectors are used for fast, easy and reliable connection and distribution of cable and conductors in electrical installation applications. The new generation of HelaCon Plus Mini wire connectors can be applied tool-free using the push-in spring technology. HelaCon Plus Mini uses a double spring which is approved for solid and stranded wires.

#### Features and Benefits

- For professional cable connections in electrical installations
- 40% smaller – Space saving design
- Low insertion force – Easy to use, saves time on installation
- Easy access to voltage test entry and innovative port shape design
- Supports installers in difficult situations like overhead work
- Correct installation can be visually checked through transparent housing
- Different colour codes for easy identification of size
- Allows different conductor diameters in each entry
- Safe application, installation and maintenance
- Practical Variobox with 350 pcs. of selected HCPM wire connectors available (148-90046)



*HelaCon Plus Mini fits perfect in every space limited situation.*



*HelaCon Plus Mini front view*

*HelaCon Plus Mini side view*

<b>MATERIAL</b>	Polycarbonate (PC)
<b>Max Current</b>	24 A
<b>Max Voltage</b>	450 V
<b>Wire Range (VDE)</b>	0.5 to 2.5 mm <sup>2</sup> solid wires / 1.0 to 2.5 mm <sup>2</sup> stranded wires
<b>Stripping Length</b>	11 mm
<b>Flammability</b>	UL94 V0
<b>Operating Temperature</b>	-30 °C to +85 °C
<b>Specifications</b>	CE, cULus, ENEC, Intertek Semko   EN 60998-2-2:2004, NEMKO AS   EN 60998-2-2:2004, SGS Fimko Ltd   EN 60998-2-2:2004



TYPE	Drawing	Number of Conductors	Colour	Width (W)	Height (H)	Depth (D)	Pack Cont.	Article-No.
HCPM-2		2	Yellow (YE)	10.8	7.7	16.5	150 pcs.	148-90036
HCPM-3		3	Orange (OG)	15.1	7.7	16.5	100 pcs.	148-90037
HCPM-4		4	Transparent (CL)	19.4	7.7	16.5	100 pcs.	148-90038
HCPM-5		5	Blue (BU)	23.7	7.7	16.5	75 pcs.	148-90039
HCPM-6		6	Violet (VT)	28.0	7.7	16.5	50 pcs.	148-90040
HCPM-8		8	Black (BK)	36.6	7.7	16.5	50 pcs.	148-90041

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval.