




Terminal Pino Tubular Simples (Ilhós)



MATERIAL	Cobre Estanhado e PVC
Tensão de Trabalho	750V
Flamabilidade	UL94V0 (antichama)

bitola	D1 (mm)	D2 (mm)	Sem Isolação	Com Isolação	L1 (mm)	L2 (mm)	Cor
0,50mm ² 20 AWG	1,40	2,60	-	HES20050-1	14,00	8,00	
0,75mm ² 18 AWG	1,87	2,80	HESS18075	HES18075-1	14,00	8,00	
1,00mm ² 17 AWG	2,00	3,00	HESS16100	HES16100-1	14,00	8,00	
1,50mm ² 16 AWG	2,30	3,50	HESS14150	HES14150-1	15,00	9,00	
2,50mm ² 14 AWG	2,60	4,20	HESS12250	HES12250-1	17,00	11,00	
4,00mm ² 12 AWG	3,50	4,80	HESS10400	HES10400-1	19,00	11,00	
6,00mm ² 10 AWG	4,00	6,30	HESS8600	HES8600-1	21,00	12,00	
10,00mm ² 7 AWG	5,00	7,60	-	HES10000-1	21,50	12,00	
16,00mm ² 6 AWG	6,40	8,80	-	HES16000-1	22,50	12,00	
25,00mm ² 3 AWG	7,90	11,20	-	HES25000-1	29,00	16,00	
35,00mm ² 2 AWG	8,80	12,70	-	HES35000-1	30,00	16,00	

Embalagem: 100 peças