

Heatshrinkable moulded shapes Low Profile Right Angle Boots - HellermannTyton																																																																																																	
DRAWING No. 152064		SHT. 1 OF 1 SHTS.		THE COPYRIGHT OF THIS DRAWING IS RESERVED BY HELLERMANN TYTON. IT IS ISSUED ON CONDITION THAT IT IS NOT COPIED, REPRODUCED OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE CONSENT IN WRITING OF HELLERMANN TYTON.				THIRD ANGLE PROJECTION		BS 8888		DO NOT SCALE IF IN DOUBT ASK		Q.A.	H/S SETT																																																																																		
														H/S Q.A.	REL. INSP.																																																																																		
														H/S PROD	EXT.ISS.CODE																																																																																		
STANDARD PART (AFTER UNRESTRICTED RECOVERY) SECTION AA														EXPANDED (AS SUPPLIED) ADHESIVE COATING, EACH END, WHEN SPECIFIED																																																																																			
FOR MOULDING PURPOSES ONLY <table><tr><th>MOULD SHAPE</th><th>øH</th><th>øJ</th><th>P</th><th>R</th><th>S</th><th>T</th><th>V</th><th>Hw</th><th>Jw</th></tr><tr><td>MAX</td><td>MAX</td><td>MAX</td><td>±6.4 (±.25)</td><td>±2.8 (±.11)</td><td>±6.4 (±.25)</td><td>±0.5 (±.02)</td><td>±0.8 (±.03)</td><td>±20%</td><td>±20%</td></tr><tr><td>333F322 *</td><td>8.9</td><td>6.1</td><td>105.2</td><td>18.5</td><td>87.6</td><td>1.3</td><td>1.5</td><td>1.5</td><td>1.5</td></tr></table>										MOULD SHAPE	øH	øJ	P	R	S	T	V	Hw	Jw	MAX	MAX	MAX	±6.4 (±.25)	±2.8 (±.11)	±6.4 (±.25)	±0.5 (±.02)	±0.8 (±.03)	±20%	±20%	333F322 *	8.9	6.1	105.2	18.5	87.6	1.3	1.5	1.5	1.5	<table><tr><th rowspan="3">PART NO.</th><th colspan="3">EXPANDED DIMENSIONS (AS SUPPLIED)</th><th colspan="2">RECOVERED DIAMETERS</th><th colspan="7">RECOVERED DIMENSIONS</th></tr><tr><th>øh</th><th>øj</th><th>p</th><th>øH</th><th>øJ</th><th>P</th><th>R</th><th>S</th><th>T</th><th>V</th><th>Hw</th><th>Jw</th></tr><tr><th>MIN</th><th>MIN</th><th>TOL</th><th>MAX</th><th>MAX</th><th>±10%</th><th>±15%</th><th>±10%</th><th>±0.8 (±.03)</th><th>+1.5,-0.8 (+.06,-.03)</th><th>+1.5,-0.8 (+.06,-.03)</th><th>±0.8 (±.03)</th></tr><tr><td>333F322-*</td><td>23.9 (.94)</td><td>17.3 (.68)</td><td>85.7 ±12.7 (3.38 ±.50)</td><td>9.9 (.39)</td><td>6.6 (.26)</td><td>105.2 (4.14)</td><td>18.5 (.73)</td><td>87.6 (3.45)</td><td>1.3 (.05)</td><td>1.5 (.06)</td><td>1.5 (.06)</td><td>1.5 (.06)</td></tr></table>								PART NO.	EXPANDED DIMENSIONS (AS SUPPLIED)			RECOVERED DIAMETERS		RECOVERED DIMENSIONS							øh	øj	p	øH	øJ	P	R	S	T	V	Hw	Jw	MIN	MIN	TOL	MAX	MAX	±10%	±15%	±10%	±0.8 (±.03)	+1.5,-0.8 (+.06,-.03)	+1.5,-0.8 (+.06,-.03)	±0.8 (±.03)	333F322-*	23.9 (.94)	17.3 (.68)	85.7 ±12.7 (3.38 ±.50)	9.9 (.39)	6.6 (.26)	105.2 (4.14)	18.5 (.73)	87.6 (3.45)	1.3 (.05)	1.5 (.06)	1.5 (.06)	1.5 (.06)
MOULD SHAPE	øH	øJ	P	R	S	T	V	Hw	Jw																																																																																								
MAX	MAX	MAX	±6.4 (±.25)	±2.8 (±.11)	±6.4 (±.25)	±0.5 (±.02)	±0.8 (±.03)	±20%	±20%																																																																																								
333F322 *	8.9	6.1	105.2	18.5	87.6	1.3	1.5	1.5	1.5																																																																																								
PART NO.	EXPANDED DIMENSIONS (AS SUPPLIED)			RECOVERED DIAMETERS		RECOVERED DIMENSIONS																																																																																											
	øh	øj	p	øH	øJ	P	R	S	T	V	Hw	Jw																																																																																					
	MIN	MIN	TOL	MAX	MAX	±10%	±15%	±10%	±0.8 (±.03)	+1.5,-0.8 (+.06,-.03)	+1.5,-0.8 (+.06,-.03)	±0.8 (±.03)																																																																																					
333F322-*	23.9 (.94)	17.3 (.68)	85.7 ±12.7 (3.38 ±.50)	9.9 (.39)	6.6 (.26)	105.2 (4.14)	18.5 (.73)	87.6 (3.45)	1.3 (.05)	1.5 (.06)	1.5 (.06)	1.5 (.06)																																																																																					
										* ALL MATERIAL CODES																																																																																							
Heatshrinkable moulded shapes Low Profile Right Angle Boots - HellermannTyton																																																																																																	
				HellermannTyton Pennycross Close, Plymouth, Devon, England Tel ++44 (0) 1752 701261 Fax ++44 (0) 1752 790058				NAME	S.Almond	SCALE	NTS	ADHESIVE	A3	SHT. 1																																																																																			
								DATE	04/04/08	DIMS IN	mm (in)		ORIGINAL SHEET SIZE 420mm x 297mm	OF 1 SHTS.																																																																																			
1	P1191	S.Almond	04/04/08					TITLE		PART No.	DRAWING No.																																																																																						
ISSUE	NOTE No.	DRAWN	DATE					RIGHT ANGLE BOOT	333F322	152064																																																																																							