

HTC Series LJ6C Module

Category 6 UTP 38.5x25mm Work Area Outlet

Application/Product Description

The HTC Series Category 6 unshielded LJ6C module is designed to support Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), 1000BASE-T (Gigabit Ethernet), 155 Mb/s ATM, Token Ring 4/16, voice/data systems and Voice over Internet Protocol (VoIP) systems running over a Category 6 cabling system and is backwards compatible with legacy Category 5e, Category 5 and voice network infrastructures.

Features and Benefits:


- Category 6 component compliant
- LJ6C 38.5x25mm footprint
- Made from ABS + PC
- Available in White
- Compatible with HTC Series 6C faceplates
- Includes mini-zip ties and instructions
- Plastic free packaging
- Bulk packed reduce carbon footprint

Technical Data


|                     |                          |    |    |
|---------------------|--------------------------|----|----|
| Style               | LJ6C                     |    |    |
| Dimensions (mm)     | H                        | W  | D  |
|                     | 38.5                     | 25 | 18 |
| Compatible Products | HTC Series 6C Faceplates |    |    |
| Material            | ABS + PC                 |    |    |
| Weight (g)          | 14                       |    |    |
| Box Quantity        | 50 pcs                   |    |    |
| Available Colours   | White                    |    |    |
| Item Code           | HTC-C6U-6C50/WH          |    |    |



HTC Series 6C Module.



HTC Series 6C Module (rear view).



HTC Series 6C Module (rear view).

Technical Features:

- Conforms to ISO 11801:2002, BS EN 50173, ANSI/TIA/EIA 568-C.2
- Compatible for both 568A / B Wiring configurations
- Minimum insertions 750
- Minimum 200 re-terminations
- Accepts 22-24 AWG conductors

Technical Diagrams

