

Description: Relicon® Pur DS is a chemical thixotropic, universally applicable two- component polyurethan waterproofing filler.

Application: For the proofing of wall break-through and other seal and filler application

Properties: Fast gelling
In a practical, transparent two- chamber pouch
Visible homogeneous mixing thanks to the patented colour change from black to grey
With SF- nozzle for optimal dosage
Very thixotropic and stable
Gas and watertight up to 1,5 bar
Excellent adhesion on all plastic cables and wires, cement and natural stone
Flexible
Scraper included
Halogen- free
No dangerous waste with homogeneous mixing of the resin
SVHC- free (contains no dangerous substances)

Processing properties:	Mixing ratio:	A:B	100:52
	Pot time	bei 23°C	15 min.

Physical properties:	Density	1,10 g/cm³	DIN EN ISO 2811-2
-----------------------------	---------	------------	-------------------

Mechanical properties: (hardened)	Temperature resistance	-25 / +110°C	
	Shore hardness D	34	EN ISO 868
	Shore hardness A	87	EN ISO 868

Usage information: The resin is delivered in a transparent two- chamber plastic pouch. Both components are separated by a middle seam. In order to protect the resin from dampness and thereby guarantee optimal durability of the products, the transparent plastic pouch is shrink-wrapped in a paper pouch laminated with aluminium. Further instructions for use and processing can be found in this data sheet or on the product packaging.

Storage: Das Relicon® PUR DS must be stored in a protective aluminium pouch at ambient temperatures of between 5°C and 40°C. When stored appropriately, the product can be stored for 24 months. The expiry date can be found on the product packaging.

Safety information: Safety information relating to the potential effects on health, safe handling, storage, usage and disposal of the product can be found on our product- specific safety data sheet.

