

Description: The parallel junction fitting PA-13 95/420 is a universal connecting and branch joint, which can be used for connections, individual and/or double branches of plastic cables and wires irrespective of the type of terminal in question.

Area of application: Parallel branch joint in low-voltage electrical systems, e.g. for street lights
Straight joint in low-voltage electrical systems, e.g. for cable repairs
Can be used universally for branching off and connecting plastic cables and wires in voltage electrical systems, e.g. for supply lines for outdoor lighting and for cable repairs
Underground, indoors, outdoors, underwater, in installations channels

Properties: Single-piece transparent moulding shell made from PP
Captive lid
Compact size
Immediately ready for use
longitudinally and transversely watertight
Joint can be cast under water

Storage: PUR 33: 48 months
Reliflex: 36 months

Included: Relicon® PUR 33 cast resin in a transparent two-chamber pouch or non-toxic Reliflex resin in a two-chamber pouch
Transparent, single-piece sleeve shell
Foam seals
Protective gloves
Emery cloth
Cleaning sponge
Assembly instructions
SF-fillers

Note: No branch terminals

Tests: CENELEC HD 631.1 S2 (PUR33)
Certified according to DIN EN 50393 (corresponds DIN VDE 0278-393)

Article-No.	Typ	Cable diameter	Conductor cross-section in mm²		Socket Dimensions A/B mm	Resin amount
		mm (from- to)	from	to		
435-00852	PA-13 95/420 Reli PP CL	Main cable 27-35	4 x 25	4 x 70	95/ 420	2045 ml / 2495 g
		Parallel outlet 21-30	4 x 10	5 x 35		
435-00152	PA-13 95/420 PUR 33 PP CL	Main cable 27-35	4 x 25	4 x 70	95/420	2045 ml / 2802 g
		Parallel outlet 21-30	4 x 10	5 x 35		



HellermannTyton

HellermannTyton GmbH
Grosser Moorweg 45
D-25436 Tömesch

Telefon: +49 (0) 4122/701-1
Telefax: +49 (0) 4122/701-400