

Description: The parallel junction fitting PAH-2 130/300 is a universal connecting and branch joint, which can be used for connections, individual and/or double branches of plastic cables and wires irrespective of the type of terminal in question.

Area of application: Can be used universally for branching off and connecting plastic cables and wires in voltage electrical systems, e.g. for house connections in residential buildings and for cable repairs
Underground, indoors, outdoors, underwater, in installations channels

Properties: Two- part, impact proof, transparent moulding shell made from PP
Compact size
Longitudinally and transversely watertight
SF- System
Immediately ready for use
Joint can be cast under water
Suitable for all compact clamping rings

Storage: PUR 33: 48 months
Reliflex: 36 months

Included: Relicon® PUR 33 cast resin in a transparent two- chamber pouch
or non- toxic Reliflex resins in transparent two- chamber pouch
Transparent, two- piece sleeve shell
Emery cloth
Cable kit, cleaning cloth
Protective gloves
Assembly instructions
Foam seals

Tests: CENELEC HD 631.1 S2 (PUR33)
Certified according to DIN EN 50393 (corresponds DIN VDE 0278-393)

Article-No.	Typ	Cable diameter	Conductor cross-section in mm²		Socket dimensions A/B	Resin amount
		mm (from- to)	from	to	mm	
435-00154	PAH-2 130/300 PP/PUR CL	Main cable 27-49	4 x 35	4 x 150	130/300	1950 ml / 2672 g
		Parallel outlet 15-33	4 x 6	4 x 70		

