


**Universal Category 6****1U 24 Port, 1U 48 Port and 2U 48 Port****Application/Product Description**

Category 6 Universal Patch Panels are designed to support Ethernet 10BASE-T, 100BASE-T (Fast Ethernet), 1000BASE-T (Gigabit Ethernet), 155 Mb/s ATM, Token Ring 4/16, voice/data systems and Voice over Internet Protocol (VoIP) systems running over a Category 6 cabling system and is backwards compatible with existing Category 5e, Category 5 and voice network infrastructures.



Universal Category 6 Patch Panels

Technical Data

Specification	Category 6								
Conformance	• ISO 11801:2002 (inc. Amend. A1 & A2) • BS EN 50173 • ANSI/TIA/EIA 568-C.2								
Wiring Specification	568A/B								
Port Density	1U 24 Port			1U 48 Port			2U 48 Port		
Dimensions (mm)	H	W	D	H	W	D	H	W	D
	44.0	483.0	34.0	44.0	483.0	91.0	88.0	483.0	29.0
Panel Weight (g)	620			1395			1395		
Outlet Style	RJ45								
RJ45 Jack Life	Minimum Insertions 1000								
Punch Down Blocks	IDC								
IDC Life	Minimum 50 re-terminations								
Wire Gauge	22-26 AWG (Maximum of 2 wires per contact).								

Material	
Panel	Mild Steel, Black Powder Coated
Modular Jack Housing	Polybutylene
Contacts	ABS/Selected Gold Plate




Performance Characteristics

Frequency (MHz)		1	100	250
Insertion Loss	Spec	3.0	18.6	31.1
	Typical	1.6	16.7	27.8
NEXT (dB)	Spec	65.0	41.8	35.3
	Typical	88.8	60.2	49.9
ACR-N (dB)	Spec	62.0	23.3	4.2
	Typical	87.2	43.5	22.2
Return Loss (dB)	Spec	19.1	14.0	10.0
	Typical	27.9	23.2	16.1
PS NEXT (dB)	Spec	62.0	39.3	32.7
	Typical	83.3	54.7	44.3
PS ACR-N (dB)	Spec	59.0	20.7	1.6
	Typical	81.7	38.0	16.5
ACR-F (dB)	Spec	64.2	24.2	16.2
	Typical	81.6	41.7	38.2
PS ACR-F (dB)	Spec	61.2	21.2	13.2
	Typical	76.5	36.6	31.5




*Typical values are for permanent link tests when using the complete HellermannTyton Data System.

**Technical Diagrams**

1U 24 Port



1U 48 Port



2U 48 Port

