




Printed copy for information only/
Ausdruck nur zur Information



Specification:

- Material: PA6.6
heatstabilized
impact modified
- Material color: black
- Hole size: 6,75 mm $\pm 0,25$
- Panel thickness: 0,7 - 5,1 mm
- Hexagonal hole: 6,35 mm $\pm 0,25$
- Panel thickness: 0,7 - 5,0 mm

Mirrored article design permitted

The manufacturing-related geometry changes (injection point, ejectors marks, etc.) allowed. Design of the details are left to suppliers discretion.

Spezifikation:

- Material: PA6.6
hitzestabilisiert,
schlagzaeh modifiziert
- Material Farbe: schwarz
- Loch Ø: 6,75 mm $\pm 0,25$
- Blechdicke: 0,7 - 5,1 mm
- Hexagonal Loch: 6,35 mm $\pm 0,25$
- Blechdicke: 0,7 - 5,0 mm

Gespiegelte Artikelausführung zulaessig

Durch das Herstellverfahren bedingte Geometrieänderungen (Anspritzung, Auswerfermarkierungen, etc.) zulaessig. Einzelheiten der Ausfuehrung bleiben dem Hersteller ueberlassen.

Revision Level			Revision Record		 		Drawn		Date (YYYY/MM/DD)		Title SOC5FT6LG				Scale	
Drawing	State	Part	Drawing frame changed; Drawing no. changed was 14.1731				G.Steiner		2004/02/03						Global Project Number	
02.4	Design Release	1				All drawing revisions are stored in CAD PDM database		Approved		Date (YYYY/MM/DD)		02-0310				
Changed	Date (YYYY/MM/DD)	Units						2004/02/03		Format		A3				
C.Cordts		2023/03/21	HellermannTyton			mm		Drawing-No 02-0310-000-CSG				Sheet				
Approved		Date (YYYY/MM/DD)				www.HellermannTyton.com						1 / 1				
B.Schiwek		2023/03/21														