

 9 ± 0.5 6.2 ± 0.5

Printed copy for information only/
Ausdruck nur zur Information

Specification:

- Material: PA6.6
heatstabilized
impact modified
- Material color: black
- Hole size: 6,2 X 12,2 mm
(-0,05/+0,15 mm)
- Panel thickness: 0,6 - 6 mm

The manufacturing-related geometry changes (injection point, ejectors marks, etc.) allowed. Design of the details are left to suppliers discretion.

Spezifikation:

- Material: PA6.6
hitzestabilisiert,
schlagzaeh modifiziert
- Material Farbe: schwarz
- Loch Ø: 6,2 X 12,2 mm
(-0,05/+0,15 mm)
- Blechdicke: 0,6 - 6 mm

Durch das Herstellverfahren bedingte Geometrieänderungen (Anspritzung, Auswerfermarkierungen, etc.) zulaessig. Einzelheiten der Ausfuehrung bleiben dem Hersteller ueberlassen.

Revision Level			Revision Record		 		The copyright of this drawing is reserved by HellermannTyton.		Drawn		Date (YYYY/MM/DD)						
Drawing	State		Part	Drawing frame changed			All drawing revisions are stored in CAD PDM database			Gerber		2011/03/16		Title		Scale 2:1	
03.3	Design Release		03		Approved					Date (YYYY/MM/DD)		Zimmermann					
Changed		Date (YYYY/MM/DD)			Units					HellermannTyton www.HellermannTyton.com		Drawing-No		08-0780-001-CSG		Format A3	
S. Dabi		2024/01/17			mm												
Approved		Date (YYYY/MM/DD)															
C. Cordts		2024/01/17															