

Tolerances	
Angle	±3°
≤6	±0.3
≤30	±0.5
≤60	±0.7
≤120	±1.5
≤400	±5
≤1000	±10
Weight 重量:	
12g	
Intended For Welded Screw Φ 焊接螺杆直径:	
M6 Torque Fixation: 10 N.m max	
Tensile Force(N) 环形拉断力:	
535N min	
Bundle Dia 捆绑直径	
Φ100 mm Max	
Material/材料:	
a: PA6 IM GF15%	
b: PA66 HIR	
Colour: Black	
c: Fast cutting steel SOM24L	
Dimension Units/尺寸单位	
mm	
PERFORMANCE/性能 SPECIFICATION/标准	

Revision NO 变更数	Revisions 变更项	Changed 修改者	Date 日期	Approved 确认者	Date 日期
①	update drawing	Sheldon Zhou	2019-08-14	Kevin Tang	2019-08-14

A-A

c: Insert metal

4 ± 0.5

20 ± 0.5

Φ 6.2 ± 0.2

a

delivery condition

Cable tie serie X120R for Φ100mm Maxi.

1.6 ± 0.2

(R 7.8)

A

A

Face crantée
Serrated side

b

(35)

(21)

1:1

17.5 ± 0.5

34.2 ± 0.5

(Φ 21)

61 ± 1

7.7 ± 0.2

①

CATIA V5

Drawn/制图

Sheldon Zhou

2019-05-13

Approved/审核

Kevin T

2019-05-13

Scale/比例

NO /无

2:1

Title/品名

X120RHDML6
Fixing Tie

Drawing-No/图号

11-0622-001-CSC

Format/格式

A3

The copyright of this drawing is reserved by
HellermannTyton.it is issued on condition that it is not
reproduced,copied or disclosed to a third party,either
wholly or in part,without the consent of
HellermannTyton.

HellermannTyton

海尔曼太通（无锡）电器配件有限公司
(WUXI) Electrical Accessories Co.,Ltd.
Tel:+86-510-5282536
Fax:+86-510-5280112