


REFERENCE:

PERFORMANCE REQUIREMENTS AT DRY AS MOLDED:

1. FIR TREE PUSH IN FORCE: REF. 10 LBS MAX IN EACH APPLICABLE OVAL HOLE SIZE AND A PLATE THICKNESS OF 1.8mm
2. FIR TREE PULL OUT FORCE: REF. 25 LBS MIN IN EACH APPLICABLE OVAL HOLE SIZE AND A PLATE THICKNESS OF 1.8mm
3. SHEET METAL THICKNESS RANGE: 0.60mm - 8.0mm
4. APPLICABLE OVAL HOLE SIZES:
 - A. 6.2 X 12.2mm
 - B. 6.5 x 12.5mm
 - C. 6.5 x 13.0mm
 - D. 7.0 x 12.0mm
5. MATERIAL: PA66HIRHS BLACK

Revision Level			Revision Record			The copyright of this drawing is reserved by HellermannTyton.		Drawn		Date (YYYY/MM/DD)	Title				Scale	
Drawing	State		Part	All drawing revisions are stored in CAD PDM database		Units mm	HellermannTyton www.HellermannTyton.com	Madere.Ni		2022/08/23	PLUGFTOVALXL (OVAL FIR TREE PLUG LONG)	2:1				
00.0	Design Release							Approved		Date (YYYY/MM/DD)		Global Project Number				
Changed		Date (YYYY/MM/DD)						Roger.Chang		2022/08/23		15-0345				
Approved		Date (YYYY/MM/DD)						Drawing-No		Format						
									15-0345-001-CSC		A4		Sheet		1 / 1	