



Technical drawing of a bolt and nut assembly. The drawing shows a bolt with a hexagonal head and a nut. Dimension lines are used to specify various parameters:

- C**: Dimension across the top of the bolt head.
- B**: Dimension across the top of the nut.
- A/F D**: Dimension across the top of the bolt head.
- MIN BORE E**: Dimension across the top of the nut.
- A**: Dimension across the top of the nut.
- A/F F**: Dimension across the top of the nut.



NOTES:

1. OPERATING TEMPERATURE
-58° F TO +275° F (-50° C TO +135° C)
2. RoHS
3. HF
4. IP RATING IP68 + IP67 + IP68+ IP69
5. FITS WITH UL360 SIZES
6. FLAMMABILITY SELF-EXTINGUISHING
(EN 61386)
7. UL LISTED TO UL514B
8. PULL-OFF TENSILE STRENGTH 265 LBS (120KG)

Material	Units: inches	The copyright of this drawing is reserved by HellermannTyton. It is issued on condition that it is not reproduced, copied, or disclosed to a third party, either wholly or in part, without the consent of HellermannTyton.	Drawn	GRW	12/1/2016	Article/Type-No	LTP-C SERIES		Scale
NICKEL PLATED BRASS & POLYAMIDE 6	Dimension without tolerances details to:		Approved	KAC	12/1/2016	Title	HELAGUARD FIXED STRAIGHT COMPRESSION FITTING FOR LTP METALLIC CONDUITS WITH LIQUID TIGHT-COVER		Project Number
	.xxxx = ±.0005		HellermannTyton North America Email: corp@htamericas.com Web: www.hellermann.tyton.com			Drawing-No	PRODUCTION : Phase	Format	AH
	.xxx = ±.005					16-1968-001-CSU		Sheet	1/1
	.xx = ±.01								
.x = ±.03									
None = ±.06									
≤ = ±0.5°									
Dimension Formatted in/[mm]									