



Printed copy for information only/
Ausdruck nur zur Information

- Performance requirements at equilibrium condition
standard atmosphere 23 °C / 50% RH

- Material color: black
- Bundle Ø: 1 - 35 mm
- Tensile force: min. 200 N
- Hole size: 4,5 to 5,0 mm
- Panel thickness: 0.7 to 8.0 mm

The manufacturing-related geometry changes (injection point, ejectors marks, etc.) allowed. Design of the details are left to suppliers discretion.

- Leistungsanforderung im Gleichgewichtszustand Normalklima 23 °C / 50% RH

- Material Farbe: schwarz
- Buendel Ø: 1 - 35 mm
- Schlaufenhaltekraft: min. 200 N
- Loch Ø: 4.5 bis 5.0 mm
- Blechdicke: 0.7 to 8.0 mm

Durch das Herstellverfahren bedingte Geometrieänderungen (Anspritzung, Auswerfermarkierungen, etc.) zulaessig. Einzelheiten der Ausfuehrung bleiben dem Hersteller ueberlassen.

Revision Level			Revision Record		 	The copyright of this drawing is reserved by HellermannTyton.		Drawn		Date (YYYY/MM/DD)		Title T30ROSASVDFT4.7LE				Scale 2:1		
Drawing	State	Part	All drawing revisions are stored in CAD PDM database	Units mm		HellermannTyton www.HellermannTyton.com		U. Villbrandt		2022/01/28						Drawing-No 19-0154-001-CSG		Global Project Number 19-0154
00.1	Design Release	00.1						Approved		Date (YYYY/MM/DD)		O. Matz		2022/01/28				Format A3
Changed		Date (YYYY/MM/DD)			Approved			Date (YYYY/MM/DD)		Sheet 1 / 1								