



1. Designed to meet push on/pull off forces of SAE/USCAR-2.
2. Arrowhead push in force: 45 newtons (10 lbf) max in each applicable sheet metal thickness.
3. Arrowhead pull out force: 110 newtons (25 lbf) min in each applicable sheet metal thickness.

1. Material: See chart
2. Material color: See chart
3. Maximum percent regrind permissible: 25%
4. Max allowable flash to be: 0.50mm
5. Max allowable mismatch to be: 0.10mm
6. Fits into USCAR clip slot specification EWCAP-005-11.
7. Applicable sheet metal thickness ranges:
  - A. 4.25mm - 4.75mm
  - B. 5.75mm - 6.25mm
8. Applicable oval hole sizes:
  - A. 12.0 x 17.0mm +/-1.0

Global Part Description	Material	Color
CC11AH12X17-PA66HIRHSUV-BK	PA66HIRHSUV	Black

Revision Level			Revision Record		   All drawing revisions are stored in CAD PDM database	The copyright of this drawing is reserved by HellermannTyton.	Drawn <b>Camosagrado</b> Approved Fish	Date (YYYY/MM/DD) 2020/01/23 Date (YYYY/MM/DD) 2020/01/23	Title 12 X 17mm arrowhead with EWCAP-005-11 connector clip	Scale 2:1 Global Project Number 19-1398
Drawing <b>00.0</b>	State Design Release	Part -	ECN 015677	Units <b>mm</b>		<b>HellermannTyton</b> <a href="http://www.HellermannTyton.com">www.HellermannTyton.com</a>	Drawing-No <b>19-1398-002-CSU</b>	Format A2 Sheet      1 / 1		
Changed	Date (YYYY/MM/DD)									
Camosagrado	2020/01/23									
Approved	Date (YYYY/MM/DD)									
Fish	2020/01/23									