





Isometric view



Isometric view
Rotated

Clip rotates
360 degrees



Reference:

Performance requirements at dry as molded:

1. Stud mount push on force: 45 newtons (10 lbf) max on each applicable stud size.
2. Stud mount pull off force: 110 newtons (25 lbf) min on each applicable stud size.

Notes:

1. Material: See chart
2. Material color: See chart
3. Maximum percent regrind permissible: 25%
4. Max allowable flash to be: 0.25mm
5. Max allowable mismatch to be: 0.1mm
6. Applicable stud size:
 - A. M5 x 0.8
 - B. T5
 - C. M6 x 1
 - D. T6

* Recommended sizes may differ depending on the application, product requirements, and materials used.


** Rotational orientation of clips upon delivery is not controlled

*** Patent: US D822,476 S, EU 003864313, CN 304373914 S

Diameter Range*		
Harness	Hose	Hard Pipe/Tube
13.0mm-15.0mm	13.0mm-15.0mm	14.0mm-15.8mm

Global Part Description	MOC14M***			Stud Mount		
	Drawing	Material	Color	Drawing	Material	Color
SMF2MOC14M-PA66HIRHSUV-BK	16-0320-000-CSU	PA66HIRHSUV	Black	19-0239-001-CSU	PA66HIRHSUV	Black

Revision Level			Revision Record				The copyright of this drawing is reserved by HellermannTyton.	Drawn	Date (YYYY/MM/DD)	Title MOC14M coupled with a M5/M6 stud mount			Scale 1:1
Drawing	State	Part	ECN 016567				Klos	2021/09/22	Approved				Date (YYYY/MM/DD)
00.0	Design Release	-			All drawing revisions are stored in CAD PDM database		Units mm	HellermannTyton		Drawing-No 19-1673-001-CSU		Format A3	
Changed	Date (YYYY/MM/DD)	2021/09/22	Klos	Date (YYYY/MM/DD)			Karabon	2021/09/22	www.HellermannTyton.com			Sheet 1 / 1	
Approved	Date (YYYY/MM/DD)	2021/09/22	Karabon	2021/09/22									



All drawing
revisions are
stored in CAD
PDM database

Units
mm

HellermannTyton
www.HellermannTyton.com

Drawing-No
19-1673-001-CSU