



- Specification:

 - Performance requirements at equilibrium condition standard atmosphere 23 °C / 50% RH
 - Material: a: PA6.6 impact resistant heatstabilized b: PA6.6 impact resistant heatstabilized
 - Material color: a: black b: black
- Spezifikation:

 - Leistungsanforderung im Gleichgewichtszustand Normalklima 23 °C / 50% RH
 - Material: a: PA6.6 schlagzaeh hitzestabilisiert b: PA6.6 schlagzaeh hitzestabilisiert
 - Material Farbe: a: schwarz b: schwarz

The manufacturing-related geometry changes (injection point, ejectors marks, etc.) allowed. Design of the details are left to suppliers discretion.

Durch das Herstellverfahren bedingte Geometrieaenderungen (Anspritzung, Auswerfermarkierungen, etc.) zulaessig. Einzelheiten der Ausfuehrung bleiben dem Hersteller ueberlassen.

Line/ Zeile	Product type/ Artikelbezeichnung	Project no./ Projektnr.	Length/ Laenge L	Strap width/ Bandbreite B	Thickness/ Dicke S	Bundle/ Buendel Ø	Tensile force/ Schlaufenhaltekraft N min.	Project no./ Projektnr.		
								Semi-finished part/ Halbfabrikat	a	b
1	T50SOSASVCOC10-14	GPN 19-1965	155 ±5	4.6 ±0.2	1.3 ±0.2	2-35	200	OC10-14	NT 044-05	GPN 17-2290

Printed copy for information only/
Ausdruck nur zur Information

Revision Level			Revision Record				The copyright of this drawing is reserved by HellermannTyton.	Drawn	Date (YYYY/MM/DD)	Title ...ASVCOC10-14			Scale 1:1
Drawing	State	Part						I. Langeloh	2020/02/17				
00.7	Design Release	00						Approved	Date (YYYY/MM/DD)	U. Villbrandt	2020/02/17	Drawing-No 19-1965-001-CSG	Format A2
Changed	Date (YYYY/MM/DD)		All drawing revisions are stored in CAD PDM database				Units mm	HellermannTyton www.HellermannTyton.com					
-	-												
Approved	Date (YYYY/MM/DD)												
-	-												