

					Revision NO 变更数	Revisions 变更项	Changed 修改者	Date 日期	Approved 确认者	Date 日期																																														
					①	Drawing Update	Robert.Zhu	20161018	Roger.Chang	20161019																																														
					②	Drawing Update	Lance.Lv	20170103	Roger.Chang	20170531																																														
					③	Drawing NO. change from16-0502 to 19-2290	Lance.Lv	20191211	Kevin.Tang	20191211																																														
	30 ± 4 ① 参考第三条要求 D B TCA xxx A L (R 1) ① (45°) C T																																																							
	<table><tr><th>项目号 PROJECT NO</th><th>Product Code 型号</th><th>Cable Range(Max.) (Φmm) 最大捆绑直径</th><th>L</th><th>T</th><th>A</th><th>B</th><th>C</th><th>D</th><th>Material 材料</th><th>Temperature Range (After Bundle) 工作温度</th></tr><tr><td>19-2290</td><td>STB152S</td><td>Φ25</td><td>152.0±2.0</td><td rowspan="7">0.26±0.01</td><td rowspan="7">4.6±0.15</td><td rowspan="7">11.0±0.3</td><td rowspan="7">(4.5)</td><td rowspan="7">6.3±0.3</td><td rowspan="7">SS316 ①</td><td rowspan="7">-80℃—+538℃</td></tr><tr><td>19-2291</td><td>STB200S</td><td>Φ50</td><td>200.0±2.0</td></tr><tr><td>19-2292</td><td>STB360S</td><td>Φ102</td><td>360.0±2.0</td></tr><tr><td>19-2293</td><td>STB520S</td><td>Φ152</td><td>520.0±2.0</td></tr><tr><td>19-2294</td><td>STB680S</td><td>Φ203</td><td>680.0±2.0</td></tr><tr><td>19-2295</td><td>STB840S</td><td>Φ254</td><td>840.0±2.0</td></tr><tr><td>19-2296</td><td>STB1050S</td><td>Φ318</td><td>1050.0±2.0</td></tr></table>										项目号 PROJECT NO	Product Code 型号	Cable Range(Max.) (Φmm) 最大捆绑直径	L	T	A	B	C	D	Material 材料	Temperature Range (After Bundle) 工作温度	19-2290	STB152S	Φ25	152.0±2.0	0.26±0.01	4.6±0.15	11.0±0.3	(4.5)	6.3±0.3	SS316 ①	-80℃—+538℃	19-2291	STB200S	Φ50	200.0±2.0	19-2292	STB360S	Φ102	360.0±2.0	19-2293	STB520S	Φ152	520.0±2.0	19-2294	STB680S	Φ203	680.0±2.0	19-2295	STB840S	Φ254	840.0±2.0	19-2296	STB1050S	Φ318	1050.0±2.0
	项目号 PROJECT NO	Product Code 型号	Cable Range(Max.) (Φmm) 最大捆绑直径	L	T	A	B	C	D	Material 材料	Temperature Range (After Bundle) 工作温度																																													
	19-2290	STB152S	Φ25	152.0±2.0	0.26±0.01	4.6±0.15	11.0±0.3	(4.5)	6.3±0.3	SS316 ①	-80℃—+538℃																																													
19-2291	STB200S	Φ50	200.0±2.0																																																					
19-2292	STB360S	Φ102	360.0±2.0																																																					
19-2293	STB520S	Φ152	520.0±2.0																																																					
19-2294	STB680S	Φ203	680.0±2.0																																																					
19-2295	STB840S	Φ254	840.0±2.0																																																					
19-2296	STB1050S	Φ318	1050.0±2.0																																																					
技术要求：② 1.带体修边后毛刺量≤5%厚度 2.尾部形状，冲裁后毛刺量≤10%厚度 3.带体中间标识TCA 316或TCA 304，需要清晰可见，不能破坏带体。																																																								
Min. Loop Tensile Strength 最低拉伸强度 670N	CAT I A V5			Drawn/制图	Robert.Zhu	2016-07-12	Scale/比例 NO /无																																																	
Dimension Units/尺寸单位 mm	The copyright of this drawing is reserved by HellermannTyton.it is issued on condition that it is not reproduced,copied or disclosed to a third party,either wholly or in part,without the consent of HellermannTyton.			HellermannTyton 海尔曼太通（无锡）电器配件有限公司 (WUXI) Electrical Accessories Co.,Ltd. Tel:+86-510-5282536 Fax:+86-510-5280112			Title/品名																																																	
PERFORMANCE/性能 SPECIFICATION/标准							Drawing-No/图号 ③ 19-2290-001-CSC			Format/格式 A3																																														