


Isometric View

- Reference:
- 1. Material: See chart
  - 2. Material color: See chart
  - 3. Min. Vertical Pull Force: 44.5N (10 lbf)
  - 4. Maximum percent regrind permissible: 10%
  - 5. Maximum allowable flash to be: 0.25mm
  - 6. Magnets are very strong. Handling them with care is necessary to prevent personal injuries, property damages and magnet damages
  - 7. Listed pull force values are based on magnet strength only. Assembled product performance will vary based on application and surface type. Please test application to determine best product fit

<div><div><div><div><div><div></div></div></div><div><div><div>UL</div><div>US</div></div></div><div><div>LISTED</div></div></div></div><div>UL Listing</div></div>		
ANSI/UL 62275	Positioning Devices TYPE 21    E64139	44N (10 lbf) Vertical Pull
All testing performed using 3mm min. thick 1008-1010 steel plate		

Global Part Description	Item No.	Qty.	Material	Finish	Color
MAGCTM10S-NDFEB35/POM/ST-WH	1	1	POM	-	White
	2	1	NdFeB N35M	NiCuNi	Silver
		1	Steel	Epoxy	White

Revision level			Revision Record				The copyright of this drawing is reserved by HellermannTyton.		Drawn		Date (YYYY/MM/DD)								
Drawing	State		Part	ECN 017476 - Initial Release			All drawing revision are stored in CAD PDM database		Johnson		2023/03/10		Title		Scale				
00.3	Design Release		-			Approved			Date (YYYY/MM/DD)										
Changed		Date (YYYY/MM/DD)				Units mm			HellermannTyton www.HellermannTyton.com		Toll		2023/04/14		Drawing-No 23-0064-001-CSU		Format A3 Sheet 1/1		
Johnson		2023/03/10																	
Approved		Date (YYYY/MM/DD)																	
Toll		2023/04/14																	