







Isometric View

- Reference:
1. Material: See chart
 2. Material color: See chart
 3. Min. Vertical Pull Force: 44.5N (10 lbf)
 4. Maximum percent regrind permissible: 10%
 5. Maximum allowable flash to be: 0.25mm
 6. Magnets are very strong. Handling them with care is necessary to prevent personal injuries, property damages and magnet damages
 7. Listed pull force values are based on magnet strength only. Assembled product performance will vary based on application and surface type. Please test application to determine best product fit

 UL Listing		
ANSI/UL 62275	Positioning Devices TYPE 21 E64139	44N (10 lbf) Vertical Pull
All testing performed using 3mm min. thick 1008-1010 steel plate		

Global Part Description	Item No.	Qty.	Material	Finish	Color
MAGCTM10S-NDFEB35/POM/ST-BK	1	1	POM	-	Black
	2	1	NdFeB N35M	NiCuNi	Silver
		1	Steel	Epoxy	Black

Revision level			Revision Record				Drawn		Date (YYYY/MM/DD)		Title		Scale				
Drawing	State	Part					Johnson		2023/03/10								
00.3	Design Release	-	ECN 017476 - Initial Release				The copyright of this drawing is reserved by HellermannTyton.		Date (YYYY/MM/DD)		Magnetic Cable Tie Mount Small, 10 lbf pull rate, Black		3:1				
Changed		Date (YYYY/MM/DD)					Approved		2023/04/14				Global Project Number				
Johnson		2023/03/10							HellermannTyton		Drawing-No		23-0064-002-CSU		23-0064		
Approved		Date (YYYY/MM/DD)													Format		
Toll		2023/04/14						www.HellermannTyton.com		23-0064-002-CSU		A3					
												Sheet					
												1/1					