











- Reference:
- Performance requirements at dry as molded:
- 1. Fir tree push in force: 45 newtons (10 lbf) max in the applicable nominal hole size and a plate thickness of 1.8mm.
 - 2. Fir tree pull out force: 110 newtons (25 lbf) min in the applicable nominal hole size and a plate thickness of 1.8mm.

- Notes:
- 1. Material: See chart
 - 2. Material color: See chart
 - 3. Maximum percent regrind permissible: 25%
 - 4. Max allowable flash to be: 0.5mm
 - 5. Max allowable mismatch to be: 0.1mm
 - 6. Sheet metal thickness range: 0.60mm - 6.00mm
 - 7. Applicable hole size:
A. 6.5mm +0.5/- 0.4

Global Part Description	Material	Color
ROC18.5-22.5FT6.5-PA66HIRHSUV-BK	PA66HIRHSUV	Black

Revision Level		
Drawing	State	Part
00.1	Design Release	-
Changed	Date (YYYY/MM/DD)	
Karabon	2024/03/22	
Approved	Date (YYYY/MM/DD)	
Van Hulst	2024/03/22	

Revision Record	
ECN 311027	

All drawing revisions are stored in CAD PDM database

The copyright of this drawing is reserved by HellermannTyton.

Drawn	Date (YYYY/MM/DD)
Karabon	2024/03/22
Approved	Date (YYYY/MM/DD)
Van Hulst	2024/03/22

Title	Ratchet O-Clamp, 18.5-22.5mm, with 6.5mm fir tree	
	Scale 1:1	
	Global Project Number 24-0496	
	Format A3	

Drawing-No
24-0496-001-CSU

Sheet	1 / 1
-------	-------