







Vertical Face Orientation
Scale 3 : 1



Downward Face Orientation
Scale 3 : 1




①




Cable tie pass-thru
See note 4

Section A-A



Ø 7.85 ±0.20
Counterbore

⑤



Cable tie CutZone

- ⑦ Performance notes:
- PA66HIRHS(REC100) performance requirements are validated at dry as molded ($\leq 0.5\%$ H₂O by weight)
 - Load testing
 - Downward Face
 - 31 N [7 lbf] minimum without cable tie
 - 67 N [15 lbf] minimum with cable tie
 - Vertical Face
 - 67 N [15 lbf] minimum without cable tie
 - Mounting screw size:
 - M4
 - #8 [0.164in]
 - Accommodates cable tie series: T18 - T120

Notes:

- Material: See chart
- Material color: See chart
- Maximum percent regrind permissible: 0%
- Maximum allowable flash to be: 0.25mm
- Maximum allowable mismatch to be: 0.10mm
- A dimension without an inspection report symbol  does not require inspection. It may be controlled on the individual component drawing.
 - Total number of inspection required: 7
 - Last number used: 7
 - Missing symbols: -

Revision level		
Drawing	State	Part
00.2	Design Release	-
Changed	Date (YYYY/MM/DD)	
Mann	2024/09/04	
Approved	Date (YYYY/MM/DD)	
Johnson	2024/09/17	

Revision Record	
ECN 311446	


All drawing revision are stored in CAD PDM database

The copyright of this drawing is reserved by HellermannTyton.	
Units	mm

Drawn	Date (YYYY/MM/DD)
Mann	2024/09/04
Approved	Date (YYYY/MM/DD)
Johnson	2024/09/17

Part Description		Material	Color
CTCM6CZS AE-PA66HIRHS(REC100)-BK		PA66HIRHS(REC100)	Black
Title		CTCM6CZS AE 6mm Cradle with Screw Mount, Retention Arms, CutZone	
Drawing-No		24-1128-001-CSU	
Scale		2:1	
Global Project Number		24-1128	
Format		A3	
Sheet		1/1	