



Non-Metallic Conduits

IWS Corrugated Tube

IWS corrugated flexible conduits are typically used to route and protect wiring in cars and commercial vehicles, control panels and machines.

Features and benefits

- Good mechanical protection and abrasion resistance
- Highly flexible
- A slit version is available on request

Slit version on request.




IWS flexible corrugated conduits

MATERIAL	Polyamide 6 (PA6)
Operating Temperature	-40 °C to +120 °C
Flammability	UL 94 HB, FMVSS 302

HF ✓

RoHS ✓



IWS non-metallic conduit

TYPE	Nominal Ø	Outside Ø (OD)	Inside Ø (ID)	Min. Bending Radius (R)	Colour	Reel Length	Article-No.
IWS4.5	4.5	7.3	4.3	8	Black (BK)	100 m	169-22450
IWS7.5	7.5	10.0	6.7	13	Black (BK)	50 m	169-22750
IWS8.5	8.5	11.7	8.4	15	Black (BK)	50 m	169-22850
IWS10	10	13.0	9.9	20	Black (BK)	50 m	169-22100
IWS12	12	15.7	12.2	30	Black (BK)	50 m	169-22120
IWS13	13	15.8	12.7	35	Black (BK)	50 m	169-22130
IWS14	14	18.5	14.2	40	Black (BK)	50 m	169-22140
IWS17	17	21.2	16.6	45	Black (BK)	50 m	169-22170
IWS19	19	24.3	19.3	50	Black (BK)	50 m	169-22190
IWS22	22	25.4	21.3	50	Black (BK)	50 m	169-22220
IWS23	23	28.3	23.2	55	Black (BK)	50 m	169-22230
IWS26	26	31.2	25.8	60	Black (BK)	25 m	169-22260
IWS29	29	34.5	29.0	65	Black (BK)	25 m	169-22290

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content.



Please note! Not all products listed on this page may have this approval. Please check our website for latest approvals.