



### Pneumatic tensioning tool metal housing

#### MK3PNSP2 up to 4.8 mm strap width

The MK3PNSP2 pneumatic bundling tool is characterized by its unique repeatability at high bundling performance. The cut end of the tie is automatically ejected. The usual work interruptions to remove the cable tie sections omitted. The pneumatic tensioning tool ensures high process reliability in production, above all in the automotive industry.

#### Features and benefits

- Pneumatic tensioning tool
- Tough metal housing
- For cable ties up to 4.8 mm width
- For consistent tensioning and automatically flush cutting
- Infinitely adjustable tension force
- High application speed
- Reliable and low maintenance



The pneumatic tensioning tool MK3PNSP2 for plastic cable ties with max. width of 4.8 mm.

<b>Air Supply</b>	non oiled, oiled
<b>Air Pressure (min.)</b>	5.5 Bar
<b>Air Pressure (max.)</b>	6 Bar
<b>Hose Internal Diameter</b>	4.0 mm
<b>L x H x W</b>	approx. 225 x 140 x 40 mm

**RoHS** ✓

TYPE	Description	Strap Width max.	Strap Thickness max.	Weight	Article-No.
<b>MK3PNSP2 with microswitch</b>	MK3PNSP2 with microswitch	4.8	1.5	0.582 kg	110-03440
<b>MK3PNSP2 with microswitch and tension lock</b>	MK3PNSP2 with microswitch and tension lock	4.8	1.5	0.568 kg	110-03460
<b>MK3PNSP2 with tension lock</b>	MK3PNSP2 with tension lock	4.8	1.5	0.582 kg	110-03420
<b>MK3PNSP2</b>	MK3PNSP2	4.8	1.5	0.555 kg	110-03400
<b>SP MK3PNSP2 air hose 3 meters</b>	Air hose, complete	-	-	0.139 kg	110-30002
<b>SP MK3PNSP2 cutting blade</b>	Replacement Blade	-	-	0.001 kg	110-30101

All dimensions in mm. Subject to technical changes.