SpotClip-Plate - Further Accessories



SpotClip-Caps offered in a pack of 4 pieces.

D max.	
D min.	
	Ţ
	OD
	l
SpotClip-Cap	

MATERIAL	Polyamide 6.6, heat stabilised (PA66HS)		
Operating Temperature	-40 °C to +105 °C		
Flammability	UL94 V2, Self extinguishing, Glow Wire Test (GWT) 960°C		

HF	RoHS

ТҮРЕ	Outside Ø (OD)	Ø D min.	Ø D max.	Colour	Pack Cont.	Article-No.
SpotClip-Caps 16/25	60.0	16.0	22.0	Black (BK)	4 pcs.	148-00118

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content.

SpotClip-Tubes



SpotClip-Cap fits into standard 25 mm diameter SpotClip-Tube.

SpotClip-Cap with 25 mm diameter SpotClip-Tube

MATERIAL	Flexible Polyvinyl Chloride (PVC)			
Operating Temperature	-5 °C to +60 °C			

	. /
RoHS	
иопэ	

ТҮРЕ	Length (L)	Ø D max.	Colour	Pack Cont.	Article-No.
SpotClip-Tubes	200.0	25.0	Grey (GY)	4 pcs.	148-00131

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content.

