



### High Temperature Tapes – Arc and Fireproofing Tape

#### HelaTape Power 410



HelaTape Power 410 is an unsupported, linerless, elastomeric tape used for arc and flame protection.

#### Features and benefits

- Unsupported, linerless, elastomeric tape
- Superior arc and flame proofing for high voltage and communication cables
- For cable protection in cable trays, switch boxes, cable conduits and substations
- Excellent flexibility and conformability for easy application
- Creates insulating residue when exposed to severe flame conditions
- Passes flammability test according to Con-Ed EO 5343-14
- Withstands Bunsen burner flame for many minutes
- Water, chemical and UV resistant

<b>MATERIAL</b>	Elastomer (PM)
<b>Elongation at break</b>	300 %

RoHS ✓

#### HelaTape Power 410

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HTAPE-POWER410	0.76	38.0	6.0 m	Grey (GY)	711-10100

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.

#### HelaTape Power 600

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HTAPE-POWER600-19x6.7	0.76	19.0	6.7 m	Black (BK)	711-10200
HTAPE-POWER600-38x6.7	0.76	38.0	6.7 m	Black (BK)	711-10201

All dimensions in mm. Subject to technical changes.  
Minimum Order Quantity (MOQ) may differ from package content.

### Self-amalgamating Tapes – Low Voltage Rubber Tape

#### HelaTape Power 600



HelaTape Power 600 is a self-amalgamating low voltage rubber tape.

#### Features and benefits

- Self-amalgamating low voltage rubber tape
- Primary insulation at not more than 1 kV
- Easily suitable to irregular shapes and surfaces
- Compatible with all extruded dielectric cable insulations
- Weather resistant and flame retardant according to UL 510
- Recommended use in conjunction with HelaTape Flex for mechanical protection

<b>MATERIAL</b>	Natural Rubber (NR)
<b>Operating Temperature</b>	+80 °C
<b>Intermittent Operating Temperature</b>	+95 °C
<b>Tensile Strength</b>	2 N/mm <sup>2</sup>
<b>Elongation at break</b>	300 %
<b>Dielectric Strength</b>	14 kV/mm

HF ✓

RoHS ✓