



Self-amalgamating Tapes – Medium Voltage Rubber Tape (Linerless)

HelaTape Power 715

The rubber-based self-amalgamating linerless tape is used for electrical insulation, protection, sealing, splicing and termination of cables up to 35 kV. The special material comes without a separating liner and reduces therefore the time required to apply the tape. It features with excellent UV, moisture, corrosion, ozone and chemical resistance. HelaTape Power 715 is compatible with all extruded dielectric cable insulations.

Features and benefits

- Rubber-based self-amalgamating linerless tape
- Used for waterproof sealing and corrosion protection of cables
- Excellent electrical insulation and weather protection
- Time saving application without liner
- Easy to apply and very flexible



HelaTape Power 715 allows quicker layering due to the linerless composition.

MATERIAL	Ethylene Propylene Rubber (EPR)
Operating Temperature	+90 °C
Intermittent Operating Temperature	+130 °C
Water Absorption	0.06 %
Tensile Strength	2.1 N/mm ²
Elongation at break	700 %
Volume Resistance	10 ¹⁶ Ω cm
Dielectric Strength	30 kV/mm

HF ✓

RoHS ✓

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HTAPE-POWER715-19x5	0.50	19.0	5.0 m	Black (BK)	711-00310
HTAPE-POWER715-19x10	0.50	19.0	10.0 m	Black (BK)	711-00311
HTAPE-POWER715-25x10	0.50	25.0	10.0 m	Black (BK)	711-00312

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.