

Shrinkable markers "Ladder Style", thermal transfer

THTT DS – 2:1 Aerospace High Temperature "Ladder Style"

THTT is a 2:1 high temperature, flame retardant heat shrink marker. The material is pre-cut and formatted into a convenient "ladder" system that allows printing on both sides of the marker.

The printed marker is ideal for use in applications where high temperature and exposure to aggressive solutions are found. The pre-cut format not only allows printing on both sides of the marker but the user can also easily choose and pick each required marker. The tubing has been especially prepared so that the print performance is excellent at all times using HellermannTyton's printer range.

The material is also especially formulated to be printable with laser beam printers.

Features and benefits

- Shrink ratio 2:1
- PVDFX high temperature marker
- Thermal transfer or laser beam printable
- 50 mm and 25 mm pre-cut marker options as standard, other lengths available on request
- Available in black and white as standard
- Good mechanical strength and highly flexible
- Delivery in convenient storage boxes



THTT DS - High temperature heatshrink printable marker.

MATERIAL	Polyvinylidene Fluoride cross-linked (PVDFX)
Operating Temperature	-55 °C to +225 °C
Min. Shrink Temperature	+120 °C
Shrink Ratio	2:1
Recommended Ribbon Type	TTRHT
Thermal Transfer Printer	TT430, TT4030, TrakMark DS

RoHS ✓



For size matrix please refer to page 439.

TYPE	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Pack Cont.	Colour	Article-No.
THTT24DS-2X25BK	2.4	1.2	25.0	0.41	2,000 pcs.	Black (BK)	553-72519
THTT24DS-2X25WH	2.4	1.2	25.0	0.41	2,000 pcs.	White (WH)	553-72501
THTT24DS-1X50BK	2.4	1.2	50.0	0.41	1,000 pcs.	Black (BK)	553-72518
THTT24DS-1X50WH	2.4	1.2	50.0	0.41	1,000 pcs.	White (WH)	553-72500
THTT32DS-2X25BK	3.2	1.6	25.0	0.27	2,000 pcs.	Black (BK)	553-72521
THTT32DS-2X25WH	3.2	1.6	25.0	0.27	2,000 pcs.	White (WH)	553-72503
THTT32DS-1X50BK	3.2	1.6	50.0	0.27	1,000 pcs.	Black (BK)	553-72520
THTT32DS-1X50WH	3.2	1.6	50.0	0.27	1,000 pcs.	White (WH)	553-72502

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.



Shrinkable markers "Ladder Style", thermal transfer

THTT DS – 2:1 Aerospace High Temperature "Ladder Style"



TYPE	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Pack Cont.	Colour	Article-No.
THTT48DS-2X25BK	4.8	2.4	25.0	0.27	2,000 pcs.	Black (BK)	553-72523
THTT48DS-2X25WH	4.8	2.4	25.0	0.27	2,000 pcs.	White (WH)	553-72505
THTT48DS-1X50BK	4.8	2.4	50.0	0.27	1,000 pcs.	Black (BK)	553-72522
THTT48DS-1X50WH	4.8	2.4	50.0	0.27	1,000 pcs.	White (WH)	553-72504
THTT64DS-2X25BK	6.4	3.2	25.0	0.33	2,000 pcs.	Black (BK)	553-72525
THTT64DS-2X25WH	6.4	3.2	25.0	0.33	2,000 pcs.	White (WH)	553-72507
THTT64DS-1X50BK	6.4	3.2	50.0	0.33	1,000 pcs.	Black (BK)	553-72524
THTT64DS-1X50WH	6.4	3.2	50.0	0.33	1,000 pcs.	White (WH)	553-72506
THTT95DS-2X25BK	9.5	4.8	25.0	0.33	1,000 pcs.	Black (BK)	553-72527
THTT95DS-2X25WH	9.5	4.8	25.0	0.33	1,000 pcs.	White (WH)	553-72509
THTT95DS-1X50BK	9.5	4.8	50.0	0.33	500 pcs.	Black (BK)	553-72526
THTT95DS-1X50WH	9.5	4.8	50.0	0.33	500 pcs.	White (WH)	553-72508
THTT127DS-2X25BK	12.7	6.4	25.0	0.33	1,000 pcs.	Black (BK)	553-72529
THTT127DS-2X25WH	12.7	6.4	25.0	0.33	1,000 pcs.	White (WH)	553-72511
THTT127DS-1X50BK	12.7	6.4	50.0	0.33	500 pcs.	Black (BK)	553-72528
THTT127DS-1X50WH	12.7	6.4	50.0	0.33	500 pcs.	White (WH)	553-72510
THTT190DS-2X25BK	19.1	9.5	25.0	0.43	1,000 pcs.	Black (BK)	553-72531
THTT190DS-2X25WH	19.1	9.5	25.0	0.43	1,000 pcs.	White (WH)	553-72513
THTT190DS-1X50BK	19.1	9.5	50.0	0.43	500 pcs.	Black (BK)	553-72530
THTT190DS-1X50WH	19.1	9.5	50.0	0.43	500 pcs.	White (WH)	553-72512
THTT254DS-2X25BK	25.4	12.7	25.0	0.48	600 pcs.	Black (BK)	553-72533
THTT254DS-2X25WH	25.4	12.7	25.0	0.48	600 pcs.	White (WH)	553-72515
THTT254DS-1X50BK	25.4	12.7	50.0	0.48	300 pcs.	Black (BK)	553-72532
THTT254DS-1X50WH	25.4	12.7	50.0	0.48	300 pcs.	White (WH)	553-72514
THTT381DS-2X25BK	38.1	19.1	25.0	0.50	200 pcs.	Black (BK)	553-72535
THTT381DS-2X25WH	38.1	19.1	25.0	0.50	200 pcs.	White (WH)	553-72517
THTT381DS-1X50BK	38.1	19.1	50.0	0.50	100 pcs.	Black (BK)	553-72534
THTT381DS-1X50WH	38.1	19.1	50.0	0.50	100 pcs.	White (WH)	553-72516

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.