



### Manual tensioning tool for KR-Series

#### KR6/8

Application tool KR6/8 crimps the glass-fibre-reinforced locking pin of the KR seal and leads to plastic deformation of the tie ends. This produces a very proof permanent connection. In combination with KR cable ties this system offers high vibration resistance. One reason for customers in the railway and automotive industry to take this system as a preferred solution.

#### Features and benefits

- Tough metal tool for applying KR cable ties only
- For tensioning, fixing and cutting KR cable ties
- Simply change the front plate to apply 6 mm or 8 mm straps



The manual tensioning tool KR6/8 for KR-Series cable ties.

| TYPE                       | Description       | For Ties | Strap Width max. | Weight  | Article-No. |
|----------------------------|-------------------|----------|------------------|---------|-------------|
| KR6/8                      | KR6/8             | KR6, KR8 | 8.0              | 0.52 kg | 121-00680   |
| SP KR6/8 replacement blade | Replacement blade | KR6, KR8 | -                | 0.01 kg | 122-68019   |

All dimensions in mm. Subject to technical changes.

### Pneumatic tensioning tool for KR8-Series

#### KR8PNSE

Application tool KR8PNSE crimps the glass-fibre-reinforced locking pin of the KR seal and leads to plastic deformation of the tie ends. This produces a very proof permanent connection.

#### Features and benefits

- Pneumatic tool with tough metal housing
- For applying KR8 cable ties only
- For tensioning, fixing and automatically cutting KR8 cable ties
- Tension force can be adapted in reliance on air pressure
- Holding ring for a balancer



The pneumatic tensioning tool KR8PNSE for KR-Series cable ties.

|                               |                           |
|-------------------------------|---------------------------|
| <b>Air Supply</b>             | non oiled / oiled         |
| <b>Air Pressure (min.)</b>    | 3 Bar                     |
| <b>Air Pressure (max.)</b>    | 4 Bar                     |
| <b>Hose Internal Diameter</b> | 6.0 mm                    |
| <b>L x H x W</b>              | approx. 320 x 210 x 50 mm |

RoHS

| TYPE                         | Description       | For Ties | Strap Width max. | Weight  | Article-No. |
|------------------------------|-------------------|----------|------------------|---------|-------------|
| KR8PNSE                      | KR8PNSE           | KR8      | 8.0              | 1.56 kg | 121-00889   |
| SP KR8PNSE replacement blade | Replacement Blade | KR8      | -                | 0.01 kg | 122-80032   |

All dimensions in mm. Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.