



### Cable ties with ball-lock and coating

#### MBT-FC-Series, stainless steel 316

The MBT range of stainless steel cable ties can be used in the most arduous of conditions or where the additional security, strength and fire resistance of a metal fixing is required. Used in all industries from mass transit, ship building, oil rigs, mining and chemical industry, theatres and exhibition halls. In the event of a fire, cables will remain securely held in place and will not fall to block emergency exits. Fully coated ties can also be used to avoid any reflection. An important consideration for instance in the defence industry.

#### Features and benefits

- Fully coated MBT, made from type 316 stainless steel with polyester coating
- Non-releasable locking feature
- Coated cable tie with smooth edges
- Comfortable handling and installation
- Eliminates contact corrosion between dissimilar materials during application



The MBT-Series (up to 7.9 mm) can be used in combination with the stainless steel P-Mount. The mount is simple to install with a screw or bolt and ensures a durable fixing solution. Please see page 163.




Material specification please see page 23.




Stainless steel cable ties, coated, MBT\_SFC, MBT\_HFC.




Stainless steel cable ties, coated, MBT\_XHFC.



MBT-Series 4.6 mm and 7.9 mm width

TYPE	Width (W)	Length (L)	Bundle Ø min.	Bundle Ø max.		Material	Pack Cont.	Tools	Article-No.
MBT5SFC	4.6	127	15	25	540	SS316, SP	100 pcs.	15-18	111-00288
MBT8SFC	4.6	201	17	50	540	SS316, SP	100 pcs.	15-18	111-00289
MBT14SFC	4.6	362	17	102	540	SS316, SP	100 pcs.	15-18	111-00290
MBT20SFC	4.6	521	17	152	540	SS316, SP	100 pcs.	15-18	111-00291
MBT27SFC	4.6	681	17	203	540	SS316, SP	100 pcs.	15-18	111-00292
MBT33SFC	4.6	838	17	254	540	SS316, SP	100 pcs.	15-18	111-00293
MBT8HFC	7.9	201	17	50	1,020	SS316, SP	50 pcs.	15-18	111-00294
MBT14HFC	7.9	362	17	102	1,020	SS316, SP	50 pcs.	15-18	111-00295
MBT20HFC	7.9	521	17	152	1,020	SS316, SP	50 pcs.	15-18	111-00296
MBT27HFC	7.9	681	17	203	1,020	SS316, SP	50 pcs.	15-18	111-00297
MBT33HFC	7.9	838	17	254	1,020	SS316, SP	50 pcs.	15-18	111-00298

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

Recommended Tools				
	15	16	17	18
	MK9SST	MK9PSST	HDT16	KST-STG200
	604	604	605	605

For more information on toolings please refer to the Application Tooling chapter.