Cable Ties and Fixings

## Cable Ties with punch-locking mechanism

## MST-Series, stainless steel 304

Stainless steel cable ties are designed for fixing loads and cables securely in hazardous industrial environments such as railway carriages, jet engines, inside power plants or on offshore drilling platforms, where exposure to extremes of weather, saltwater and temperature are common. The MST-Series tie with its new punch-locking mechanism is an excellent choice especially for environments which require high resistance to vibrations.

## **Features and benefits**

- MST-Series cable ties are made from stainless steel 304
- · No loosening after bundling
- · Corrosion and weather resistant
- · Significantly improved vibration resistance
- · Outstanding chemical resistance
- · Space saving solution
- · Safe cut-off (no sharp edges)
- High temperature resistant
- Non-burning



One Step to the Web!




Stainless Steel Cable Ties MST-Series.

The MST-Series (up to 8.9 mm) can be used in combination with the stainless steel P-Mount. The mount is simple to install with a screw or bolt and ensures a durable fixing solution. Please see page 163.



Can support quality assurance in the production of food stuffs, for example HACCP.



| MSI | tie |  |
|-----|-----|--|
|     |     |  |

| TYPE    | Width<br>(W) | Length<br>(L) | Bundle Ø<br>min. | Bundle Ø<br>max. | Z     | Material | Pack<br>Cont. | Tools | Article-No. |
|---------|--------------|---------------|------------------|------------------|-------|----------|---------------|-------|-------------|
| MST200S | 5.9          | 207.0         | 5.0              | 50.0             | 900   | SS304    | 100 pcs.      | 19    | 111-01549   |
| MST360S | 5.9          | 360.0         | 5.0              | 100.0            | 900   | SS304    | 100 pcs.      | 19    | 111-01550   |
| MST500S | 5.9          | 500.0         | 5.0              | 145.0            | 900   | SS304    | 100 pcs.      | 19    | 111-01551   |
| MST700S | 5.9          | 700.0         | 5.0              | 205.0            | 900   | SS304    | 100 pcs.      | 19    | 111-01552   |
| MST360M | 8.9          | 369.0         | 8.0              | 100.0            | 1,500 | SS304    | 50 pcs.       | 20    | 111-01631   |
| MST500M | 8.9          | 509.0         | 8.0              | 145.0            | 1,500 | SS304    | 50 pcs.       | 20    | 111-01632   |
| MST700M | 8.9          | 700.0         | 8.0              | 205.0            | 1,500 | SS304    | 50 pcs.       | 20    | 111-01633   |

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

| Recommended Tools |      |      |  |  |  |
|-------------------|------|------|--|--|--|
|                   | 19   | 20   |  |  |  |
|                   | MST6 | MST9 |  |  |  |
|                   | 606  | 606  |  |  |  |

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.