




## 1-Piece Fixing Ties for Weld Studs

### LFC-Series for routing close to the stud

#### Features and Benefits

- 1-piece fixing tie for 5 mm studs
- Cable tie head always situated in defined position
- Easy to install without the need for a tool
- Bundle runs very close next to stud
- Closed stud retainer protects the bundle against damage
- Contact surface allows secure bundling with tensioning tool



LFC165-2 can be put on by hand.



LFC165-2 for bundle diameters up to 35.0 mm



**Material specification  
please see page 22.**

| TYPE        | Width (W) | Length (L) | Bundle Ø max. | N   | Stud Ø | Material | Colour     | Tools | Article-No. |
|-------------|-----------|------------|---------------|-----|--------|----------|------------|-------|-------------|
| LFC155      | 4.6       | 163.0      | 26.0          | 160 | 5.0    | PA66     | Black (BK) | 2-10  | 131-60070   |
| LFC165(PSA) | 4.7       | 165.0      | 35.0          | 90  | 5.0    | PA66HS   | Black (BK) | 2-10  | 155-34202   |
| LFC165-2    | 4.7       | 165.0      | 35.0          | 150 | 5.0    | PA66HS   | Black (BK) | 2-10  | 157-00047   |

All dimensions in mm. Subject to technical changes.


## 1-Piece Fixing Ties for Weld Studs, for Heavy Duty Applications

### WS-Series for threaded studs

Wide strap stud-mounted cable ties are primarily designed for use in the automotive or truck industry.

#### Features and Benefits

- Very flexible strap provides minimum pinching of soft hoses and convoluted tubing
- Low profile head for compact bundling
- Clamping rails to increase grip on round bundles
- Flexible hinge



Wide Strap Heavy Duty Stud Mount Cable Ties



The wide strap stud mount cable tie minimizes pinching on soft bundles.

| TYPE  | Width (W) | Length (L) | Bundle Ø max. | N   | Stud Ø | Material    | Colour     | Tools | Article-No. |
|-------|-----------|------------|---------------|-----|--------|-------------|------------|-------|-------------|
| WSS25 | 12.7      | 236.0      | 57.0          | 534 | 6.35   | PA66HIRHSUV | Black (BK) | 11-12 | 157-00400   |
| WSI25 | 12.7      | 322.6      | 82.5          | 534 | 6.35   | PA66HIRHSUV | Black (BK) | 11-12 | 157-00401   |
| WSI38 | 12.7      | 322.6      | 82.5          | 534 | 9.52   | PA66HIRHSUV | Black (BK) | 11-12 | 157-00404   |
| WSR25 | 12.7      | 389.0      | 104.1         | 534 | 6.35   | PA66HIRHSUV | Black (BK) | 11-12 | 157-00402   |

All dimensions in mm. Subject to technical changes.