



1-Piece Fixing Ties with Arrowhead, with Disc

With a diverse range of fixing possibilities these ties are ideal for use in many different industries, including automotive, aerospace, white goods manufacture and panel building.

Features and benefits

- Easy to install without the need for a tool
- Arrowhead simply locks into place
- Disc adjusts tie for pressures from various directions and minimises access of dust, dirt and water
- Cable tie head always situated in a defined position
- KSFT-types with specially rounded arrowhead minimise the assembly height




The Disc at the head of the T50SOSSFT6.5E protects the bore against dirt and splashes.




Material specification
please see page 22.

1-Piece Fixing Ties with Arrowhead, with Disc, for round holes



T50SOSKSFT5.4E



T50SOSSFT6.5E

T50SOSKSFT6.5E

TYPE	Width (W)	Length (L)	Bundle Ø max.	N	Disc Ø	Hole Ø (FH)	Panel Thickness	Material	Colour	Tools	Article-No.
PT2ASFT6.5PT0.7-1.5-E	3.4	112.7	20.0	230	16.0	6.3 - 6.7	0.7 - 1.5	PEEK	Beige (BGE)	2;4-6	126-00183
T30SOS-AS-SFT6.5-E	3.5	126.4	25.0	200	16	6.5 - 7.0	0.8 - 1.5	PA66HS	Black (BK)	2;4-6	126-00255
T50SOSAH7S-E	4.6	161.6	35.0	180	16.0	7.0	0.6 - 3.2	PA66HS	Black (BK)	2-10	126-00249
T50SOSKSFT5SE	4.6	156.0	35.0	180	16.0	4.8 - 5.2	0.7 - 1.3	PA66HS	Natural (NA)	2-10	126-00111
	4.6	156.0	35.0	180	16.0	4.8 - 5.2	0.7 - 1.3	PA66HS	Black (BK)	2-10	126-00099
T50SOSKSFT5.4E	4.6	156.0	35.0	180	16.0	5.2 - 5.6	0.7 - 1.3	PA66HS	Black (BK)	2-10	126-00075
T50SOSKSSFT5.4E-MD	4.6	156.0	35.0	180	16.0	5.4	0.7 - 1.3	PA66HS	Black (BK)	2-10	126-00180
T50SOSKSFT6.5E	4.6	156.0	35.0	180	16.0	6.3 - 6.7	0.7 - 1.3	PA66HS	Black (BK)	2-10	126-00081
T50SOSKSFT6.5S2-E	4.6	157.5	35.0	225	16.0	6.3 - 6.7	1.7 - 2.3	PA66HS	Black (BK)	2-10	126-00219
T50SOSSFT6.5E	4.6	158.8	30.0	225	16.0	6.3 - 6.7	1.9 - 2.5	PA66HS	Black (BK)	2-10	126-03102
T50SOSSFT6.5E-MD	4.6	158.8	30.0	180	16.0	6.3 - 6.7	0.6 - 1.8	PA66HS	Green (GN)	2-10	126-00216
	4.6	158.8	30.0	180	16.0	6.3 - 6.7	0.6 - 1.8	PA66HS	Black (BK)	2-10	126-00215
	4.6	158.8	30.0	180	16.0	6.3 - 6.7	0.6 - 1.8	PA66HS	Natural (NA)	2-10	126-00242
T50SL8	4.6	165.0	35.0	225	20.0	8.0	0.8 - 1.5	PA66	Black (BK)	2;4-6;8	126-01900
T50SST5	4.6	170.0	31.0	225	16.2	6.1 - 6.5	0.7 - 1.5	PA66	Natural (NA)	2-10	126-02300
	4.6	170.0	31.0	225	16.2	6.1 - 6.5	0.7 - 1.5	PA66HS	Black (BK)	2-10	126-00017
T50SD6	5.0	160.0	31.0	200	18.0	6.3 - 7.5	0.6 - 1.8	PA66HS	Black (BK)	2-10	111-85350
T50MD7	5.0	225.0	59.0	225	16.0	6.8 - 7.2	0.8 - 2.0	PA66HS	Black (BK)	2-10	111-85850
	5.0	225.0	59.0	225	16.0	6.8 - 7.2	0.8 - 2.0	PA66	Black (BK)	2-10	126-00181
OS180AH7S-LH-E	5.3	178.4	30.0	180	16.0	6.8 - 7.2	0.6 - 3.2	PA66HS	Black (BK)	2-10	126-00310

All dimensions in mm. Subject to technical changes.