



1-Piece Fixing Ties with Arrowhead, with Wings

For bundling and fixing of cable harnesses, pipes and hoses in many different industries, including automotive, aerospace, white goods manufacturing and panel building.


Features and benefits

- Easy to assemble without the need for a tool
- Cable tie head always situated in defined position
- Arrowhead simply locks into place
- Supporting legs provide a secure and firm fixing in areas where space is limited



A wide range of arrowhead fixing ties which are suitable for different panel thicknesses and hole diameters.

1-Piece Fixing Ties with Arrowhead, with Wings, for Round Holes



T50SSL5

TYPE	Drawing	Width (W)	Length (L)	Bundle Ø max.	N	Hole Ø (FH)	Panel Thickness	Material	Colour	Tools	Article-No.	
T18RWPM		2.5	113.0	22.0	80	4.8 - 5.6	1.5 - 2.2	PA66	Black (BK)	2;4-6	126-00077	
		2.5	113.0	22.0	80	4.8 - 5.6	1.5 - 2.2	PA66	Natural (NA)	2;4-6	126-00078	
		2.5	113.0	22.0	80	4.8 - 5.6	1.5 - 2.2	PA66HS	Black (BK)	2;4-6	126-00232	
T18RSF		2.5	100.0	16.0	80	4.6 - 4.8	0.8 - 3.0	PA66HS	Natural (NA)	2;4-6	111-85519	
		2.5	100.0	16.0	80	4.6 - 4.8	0.8 - 3.0	PA66W	Black (BK)	2;4-6	111-85560	
		2.5	100.0	16.0	80	4.6 - 4.8	1.0 - 3.0	PA46	Grey (GY)	2;4-6	126-00275	
T50SSL5		4.6	135.0	27.0	200	6.1 - 6.5	0.5 - 2.7	PA66HS	Black (BK)	2-10	126-02204	
		4.6	135.0	27.0	225	6.1 - 6.5	0.5 - 2.7	PA46	Grey (GY)	2-10	111-85395	
		4.6	135.0	27.0	225	6.1 - 6.5	0.5 - 2.7	PA66	Natural (NA)	2-10	111-85339	
T50SL5		4.6	163.0	34.0	222	6.1 - 6.5	0.8 - 2.7	PA66HIRHS	Black (BK)	2-10	126-00005	
		4.6	163.0	34.0	222	6.1 - 6.5	0.8 - 2.7	PA66HS	Black (BK)	2-10	126-00001	
		4.6	165.0	34.0	222	6.1 - 6.5	0.8 - 2.7	PA66	Natural (NA)	2-10	111-85369	
T50SL6		4.6	165.0	34.0	225	6.3 - 7.5	0.5 - 2.5	PA66	Black (BK)	2-10	111-85460	
T50SL7		4.6	165.0	34.0	225	6.9 - 7.1	0.8 - 2.5	PA66	Natural (NA)	2-10	111-85479	
		4.6	160.0	35.0	222	6.0 - 6.6	0.7 - 3.0	PA66	Natural (NA)	2-10	111-85739	
T50SSF		4.6	160.0	35.0	222	6.0 - 6.6	0.7 - 3.0	PA66HS	Black (BK)	2-10	126-00125	
		4.6	160.0	35.0	222	6.0 - 6.6	0.7 - 3.0	PA66HS	Natural (NA)	2-10	126-01104	
		4.6	205.0	45.0	225	6.0 - 6.6	0.7 - 3.0	PA66HS	Natural (NA)	2-10	111-85720	
OS130		5.0	130.0	20.0	147	6.8 - 7.2	0.6 - 2.6	PA66W	Black (BK)	2-10	126-00060	
T50SAH		4.6	160.0	25.0	225	6.0 - 6.6	0.7 - 3.0	PA66HS	Natural (NA)	2-10	155-41102	
		4.6	160.0	25.0	225	6.0 - 6.6	0.7 - 3.0	PA66HS	Black (BK)	2-10	126-00163	

All dimensions in mm. Subject to technical changes.