



Heat shrinkable tubing 2:1 - PVC

LVR

LVR can be used for cable joints, low voltage bus bars and batteries.


Features and benefits

- PVC heat shrinkable tubing
- Self-extinguishing
- Good chemical resistance and mechanical protection



LVR used for mechanical protection.

MATERIAL	Flexible Polyvinyl Chloride, cadmium free (PVC)
Shrink Ratio	2:1
Operating Temperature	-30 °C to +105 °C
Min. Shrink Temperature	+135 °C
Longitudinal change after shrinkage	+/-10 % max
Dielectric Strength	15 kV/mm according to IEC 243
Shelf Life	12 months
Storage Temperature	+25 °C max.
Flammability	ASTM D2671, UL224 VW-1



Heat Shrinkable Tubing 2:1

RoHS

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Tools	Article-No.
LVR-2.4/1.2	2.4	1.2	0.40	250 m	Black (BK)	30-32	344-00240
LVR-3.2/1.6	3.2	1.6	0.40	250 m	Black (BK)	30-32	344-00320
LVR-4.8/2.4	4.8	2.4	0.50	250 m	Black (BK)	30-32	344-00480
LVR-6.4/3.2	6.4	3.2	0.60	250 m	Black (BK)	30-32	344-00640
LVR-9.5/4.8	9.5	4.8	0.60	125 m	Black (BK)	30-32	344-00950
LVR-12.7/6.4	12.7	6.4	0.70	75 m	Black (BK)	30-32	344-01270
LVR-19.1/9.5	19.0	9.5	0.80	100 m	Black (BK)	30-32	344-01900
LVR-25.4/12.7	25.4	12.7	1.00	100 m	Black (BK)	30-32	344-02540

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools			
	30	31	32
	H5002	H5004	E4500
	611	611	610

For more information on toolings please refer to the Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.