



Heat shrinkable tubing 2:1 - flexible and coloured

TF21

Due to its versatility TF21 is suitable for a wide range of applications like electrical insulations, mechanical protection and marking.

Features and benefits

- Thin wall, flexible polyolefin tubing
- Fast shrinking and low shrink temperature
- Meets and exceeds lots of industrial standards
- Big variety of different colours and sizes
- Flame retarded and UL224 VW1 listed



Cut lengths available on request. Please contact us!



One Step to the Web!



TF21 – available in a wide range of colours and sizes.

MATERIAL	Polyolefin, cross-linked (PO-X)
Shrink Ratio	2:1
Operating Temperature	-55 °C to +135 °C
Min. Shrink Temperature	+90 °C
Longitudinal change after shrinkage	+/- 5 %
Dielectric Strength	37 kV/mm
Flammability	ASTM D876

RoHS ✓



Heat Shrinkable Tubing 2:1

TYPE	Supplied Ø D min.	Size (imperial)	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Tools	Article-No.
TF21-1.2/0.6	1.2	3/64 "	0.6	0.41	100 m	Blue (BU)	30-32	309-20126
	1.2	3/64 "	0.6	0.41	100 m	Red (RD)	30-32	309-20122
	1.2	3/64 "	0.6	0.41	100 m	White (WH)	30-32	309-20129
	1.2	3/64 "	0.6	0.41	100 m	Yellow (YE)	30-32	309-20124
	1.2	3/64 "	0.6	0.41	300 m	Black (BK)	30-32	309-10120
TF21-1.6/0.8	1.6	1/16 "	0.8	0.43	100 m	Blue (BU)	30-32	309-20166
	1.6	1/16 "	0.8	0.43	100 m	Red (RD)	30-32	309-20162
	1.6	1/16 "	0.8	0.43	100 m	White (WH)	30-32	309-20169
	1.6	1/16 "	0.8	0.43	100 m	Yellow (YE)	30-32	309-20164
	1.6	1/16 "	0.8	0.43	300 m	Black (BK)	30-32	309-10160
TF21-2.4/1.2	2.4	3/32 "	1.2	0.51	100 m	Blue (BU)	30-32	309-20246
	2.4	3/32 "	1.2	0.51	100 m	Green-Yellow (GNYE)	30-32	309-40247
	2.4	3/32 "	1.2	0.51	100 m	Red (RD)	30-32	309-20242
	2.4	3/32 "	1.2	0.51	100 m	White (WH)	30-32	309-20249
	2.4	3/32 "	1.2	0.51	100 m	Yellow (YE)	30-32	309-20244
	2.4	3/32 "	1.2	0.51	300 m	Black (BK)	30-32	309-10240

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.