



Heat shrinkable tubing 3:1 - flexible and coloured

TF31



Heat Shrinkable Tubing 3:1

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Reel Length	Colour	Tools	Article-No.
TF31-18/6	18.0	6.0	1.00	30 m	Black (BK)	30-32	333-31800
	18.0	6.0	1.00	30 m	Blue (BU)	30-32	333-31806
	18.0	6.0	1.00	30 m	Green (GN)	30-32	333-31805
	18.0	6.0	1.00	30 m	Green-Yellow (GNYE)	30-32	333-31807
	18.0	6.0	1.00	30 m	Red (RD)	30-32	333-31802
	18.0	6.0	1.00	30 m	White (WH)	30-32	333-31809
	18.0	6.0	1.00	30 m	Yellow (YE)	30-32	333-31804
	18.0	6.0	1.00	60 m	Black (BK)	30-32	333-41800
TF31-24/8	24.0	8.0	1.20	30 m	Black (BK)	30-32	333-32400
	24.0	8.0	1.20	30 m	Blue (BU)	30-32	333-32406
	24.0	8.0	1.20	30 m	Green (GN)	30-32	333-32405
	24.0	8.0	1.20	30 m	Green-Yellow (GNYE)	30-32	333-32407
	24.0	8.0	1.20	30 m	Red (RD)	30-32	333-32402
	24.0	8.0	1.20	30 m	White (WH)	30-32	333-32409
	24.0	8.0	1.20	30 m	Yellow (YE)	30-32	333-32404
	24.0	8.0	1.20	60 m	Black (BK)	30-32	333-42400
TF31-40/13	40.0	13.0	1.25	30 m	Black (BK)	30-32	333-34000
	40.0	13.0	1.25	30 m	Blue (BU)	30-32	333-34006
	40.0	13.0	1.25	30 m	Green (GN)	30-32	333-34005
	40.0	13.0	1.25	30 m	Green-Yellow (GNYE)	30-32	333-34007
	40.0	13.0	1.25	30 m	Red (RD)	30-32	333-34002
	40.0	13.0	1.25	30 m	White (WH)	30-32	333-34009
	40.0	13.0	1.25	30 m	Yellow (YE)	30-32	333-34004
	40.0	13.0	1.25	60 m	Black (BK)	30-32	333-24000

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools			
	30	31	32
	H5002	H5004	E4500
	568	568	567

For more information on toolings please refer to the
Application Tooling chapter.



For product specific approvals and specifications please refer to the Appendix.