



Two-component polyurethane sealing mastic

RELICON PUR DS

The RELICON PUR DS cast resin is a chemically thixotropic, universal polyurethane sealing mastic. It is ideal for sealing wall feed-throughs as well as other filling and sealing applications.

Features and Benefits

- In a practical, transparent two-chamber pouch
- Colour changes from black to grey whilst mixing
- Safe-Filling system (SF)
- Very thixotropic and high stability
- Gas and water tight to 1.5 bar
- Excellent adhesion to concrete and stone. Also on polymeric cables and wires made of PVC, XLPE, PE, EPR
- Soft elastic
- Spatula included
- SVHC-free, contains no hazardous substances, the cured product can be disposed of with house hold waste
- Halogen free



Two-component polyurethane cast resin PUR DS.

MATERIAL	Polyurethane (PUR)
Colour	Grey (GY)
Operating Temperature	-25 °C to +110 °C
Mixing Ratio (weight)	100:52
Pot Life	15 min. 23 °C
Shore Hardness D	30±5
Storage Temperature	+4 °C to +40 °C
Shelf Life	24 months

HF ✓

RoHS ✓

TYPE	Resin Quantity	Article-No.
Resin-DS-B-SF	250 ml / 275 g	435-00600
	490 ml / 539 g	435-00601

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.