



Two-component silicone gel

RELICON Religel

RELICON Religel is a transparent, elastic two-component silicone gel. It is delivered in practical transparent bottles or canisters. It is particularly suited to fill junction boxes in low-voltage applications. After curing, RELICON Religel gives excellent resistance to moisture, has high insulating properties and very good chemical resistance.

Application: Electrical insulation and moisture protection for low-voltage applications, particularly suitable for insulating cables and wires in junction boxes.

Features and Benefits

- Bottles or canisters incl. measuring cup and mixing stick
- Homogenous mixture indicated by green-coloured component B
- Can be used flexibly, in smaller quantities, mixing ratio 1:1
- Excellent flow properties
- Soft elastic, vibration absorbing, removable
- Outstanding insulating properties
- Non-toxic, free of isocyanate
- SVHC-free, contains no hazardous substances, the cured product can be disposed of with house hold waste
- Halogen free



Two-component silicone gel Religel.



Two-component silicone gel Religel.

MATERIAL	Silicone gel Religel (SIG)
Colour	Transparent (CL), Green (GN)
Operating Temperature	-40 °C to +140 °C
Mixing Ratio (weight)	100:100
Gel Time	20 min. 23 °C
Pot Life	10 min. 23 °C
Density	0.97 g/cm ³ , 20 °C (DIN EN ISO 2811-2)
Dielectric Strength	>20 kV/mm
Viscosity	1000 mPa*s, 23 °C (EN ISO 2555), 1500 mPa*s, 5 °C (EN ISO 2555)
Storage Temperature	+4 °C to +40 °C
Shelf Life	Unlimited



TYPE	Pack Cont.	Article-No.
Religel	1,000 ml	435-00750
	10,000 ml	435-00751

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.