



Two-component gel

RELICON KH 100

RELICON KH 100 is a transparent, removable, saltwater resistant, flexible two-component gel based on hydrocarbon resins in trade standard cartridges. It is especially suitable for use with junction boxes in the low-voltage range, located in a humid area or in the ground. After curing, RELICON KH 100 is characterised by its excellent resistance to moisture and very good insulating properties as well as good chemical resistance. Application: Electrical insulation and moisture protection for the low-voltage networks. Particularly suitable for filling of cable junction boxes.

Features and Benefits

- Cartridge with mixing nozzle for use with standard cartridge applicator gun
- Excellent flow properties
- Soft elastic, vibration absorbing, removable
- Outstanding insulating properties
- Cures without developing heat
- Saltwater resistant
- Non-toxic, free of silicone and isocyanate
- SVHC-free, contains no hazardous substances, the cured product can be disposed of with house hold waste
- Halogen free



**Silicon
free!**



Two-component gel KH 100.

MATERIAL	Gel KH100 (KH100)
Colour	Transparent (CL)
Operating Temperature	-40 °C to +90 °C
Mixing Ratio (weight)	1:1
Pot Life	40 min. 23 °C
Density	0.95 g/cm ³ , 20 °C (DIN EN ISO 2811-2)
Dielectric Strength	>20 kV/mm
Viscosity	2000 mPa*s, 5 °C (EN ISO 2555), 1500 mPa*s, 23 °C (EN ISO 2555)
Storage Temperature	+4 °C to +40 °C
Shelf Life	18 months

HF ✓

RoHS ✓

TYPE	Pack Cont.	Article-No.
Gel-100 Mixing-Nozzle	10 pcs.	435-00806
Gel-100	250 ml	435-00805
	600 ml	435-00807

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.