

Connectors

Compression connector, tin-plated, with central buttmark for copper conductors

Galvanised compression connectors are suitable for stranded and solid copper conductors and provided with central buttmarks for precise conductor insertion.

Features and Benefits

- Suitable for copper conductors
- Optimal material and compress properties because of the annealed material
- Precise end machining for easy cable insertion
- Tin-plated connector body
- With central buttmarks for precise core insertion



Compression connector, tin-plated, with central buttmark for copper conductors

TYPE	Inside Ø (ID)	Outside Ø (OD)	Length (L)	Pack Cont.	Article-No.
Compression connector 1.5	1.8	3.3	25.0	1 pc.	435-01450
Compression connector 2.5	2.3	4.2	25.0	1 pc.	435-01451
Compression connector 4	3	5	25.0	1 pc.	435-01452
Compression connector 6	3.5	6.5	25.0	1 pc.	435-01453
Compression connector 10	4.5	7	30.0	1 pc.	435-01454
Compression connector 16	5.5	8.5	35.0	1 pc.	435-01455
Compression connector 25	7	10	40.0	1 pc.	435-01456
Compression connector 35	8.5	12	45.0	1 pc.	435-01457
Compression connector 50	10	14	50.0	1 pc.	435-01458
Compression connector 70	12	16.5	55.0	1 pc.	435-01459
Compression connector 95	13.5	18	60.0	1 pc.	435-01460
Compression connector 120	15	19.5	65.0	1 pc.	435-01461
Compression connector 150	16.5	21	70.0	1 pc.	435-01462
Compression connector 185	19	24	75.0	1 pc.	435-01463
Compression connector 240	21	26	85.0	1 pc.	435-01464
Compression connector 300	23.5	29.5	100.0	1 pc.	435-01465
Compression connector 400	27	34	100.0	1 pc.	435-01466

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.