




Shrinkable markers "Continuous Tube", thermal transfer

TULT - 3:1 Military and Electronics

TULT is a UL recognized 3:1 heat shrink marker material supplied as a continuous tube and printable on both sides. TULT's polyolefin compound has good mechanical strength and resistance to organic solvents and chemicals. The surface of the tubing has been especially prepared so that print performance is excellent at all times. HellermannTyton's printer range allow users to create a high quality print. In addition it is possible to either perforate the tubing at pre-determined lengths or fully sever the markers.

Features and benefits

- Shrink ratio 3:1
- Available in black, blue, red, white and yellow
- Cable range from 39 mm to 1 mm
- Good mechanical strength and resistance to organic solvents and chemicals
- Highly flexible
- Delivery in convenient storage boxes



TULT – 5 colours of UL recognised printable tube to cover a wide range of diameters.

MATERIAL	Polyolefin, cross-linked (PO-X)
Operating Temperature	-55 °C to +135 °C
Min. Shrink Temperature	+90 °C
Shrink Ratio	3:1
Recommended Ribbon Type	TTRC+, TTDTHOUT, TTRW, TT822OUT8
Thermal Transfer Printer	TT430, TT4030, TRAKMARK DS

RoHS



For size matrix please refer to page 475.

TYPE	Supplied Ø D min.	Recov. Ø d max.	Wall (WT)	Pack Cont.	Colour	Article-No.
TULT3-1BK	3.0	1.0	0.60	176 m	Black (BK)	553-40352
TULT3-1BU	3.0	1.0	0.60	176 m	Blue (BU)	553-40353
TULT3-1RD	3.0	1.0	0.60	176 m	Red (RD)	553-40354
TULT3-1WH	3.0	1.0	0.60	176 m	White (WH)	553-40351
TULT3-1YE	3.0	1.0	0.60	176 m	Yellow (YE)	553-40350
TULT4.8-1.6BK	4.8	1.6	0.65	110 m	Black (BK)	553-40452
TULT4.8-1.6BU	4.8	1.6	0.65	110 m	Blue (BU)	553-40453
TULT4.8-1.6RD	4.8	1.6	0.65	110 m	Red (RD)	553-40454
TULT4.8-1.6WH	4.8	1.6	0.65	110 m	White (WH)	553-40451
TULT4.8-1.6YE	4.8	1.6	0.65	110 m	Yellow (YE)	553-40450
TULT6-2BK	6.0	2.0	0.70	110 m	Black (BK)	553-40652
TULT6-2BU	6.0	2.0	0.70	110 m	Blue (BU)	553-40653
TULT6-2RD	6.0	2.0	0.70	110 m	Red (RD)	553-40654
TULT6-2WH	6.0	2.0	0.70	110 m	White (WH)	553-40651
TULT6-2YE	6.0	2.0	0.70	110 m	Yellow (YE)	553-40650
TULT9-3BK	9.0	3.0	0.80	72 m	Black (BK)	553-40952

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content. More colours on request.



For product specific approvals and specifications please refer to the Appendix.