


Shrinkable markers "Ladder Style", thermal transfer

TLFX DS - 2:1 Rail Limited Fire Hazard



TYPE	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Pack Cont.	Colour	Article-No.
TLFX48DS-1x50YE	4.8	2.4	50.0	0.64	5,000 pcs.	Yellow (YE)	553-60012
TLFX64DS-2x25WH	6.4	3.2	25.0	0.73	6,000 pcs.	White (WH)	553-60023
TLFX64DS-2x25YE	6.4	3.2	25.0	0.73	6,000 pcs.	Yellow (YE)	553-60032
TLFX64DS-1x50WH	6.4	3.2	50.0	0.73	3,000 pcs.	White (WH)	553-60003
TLFX64DS-1x50YE	6.4	3.2	50.0	0.73	3,000 pcs.	Yellow (YE)	553-60013
TLFX95DS-2x25WH	9.5	4.8	25.0	0.70	5,000 pcs.	White (WH)	553-60024
TLFX95DS-2x25YE	9.5	4.8	25.0	0.70	5,000 pcs.	Yellow (YE)	553-60033
TLFX95DS-1x50WH	9.5	4.8	50.0	0.70	2,500 pcs.	White (WH)	553-60004
TLFX95DS-1x50YE	9.5	4.8	50.0	0.70	2,500 pcs.	Yellow (YE)	553-60014
TLFX127DS-2x25WH	12.7	6.4	25.0	0.70	3,000 pcs.	White (WH)	553-60025
TLFX127DS-2x25YE	12.7	6.4	25.0	0.70	3,000 pcs.	Yellow (YE)	553-60034
TLFX127DS-1x50WH	12.7	6.4	50.0	0.70	1,500 pcs.	White (WH)	553-60005
TLFX127DS-1x50YE	12.7	6.4	50.0	0.70	1,500 pcs.	Yellow (YE)	553-60015
TLFX190DS-2x25WH	19.0	9.5	25.0	0.78	3,000 pcs.	White (WH)	553-60026
TLFX190DS-2x25YE	19.0	9.5	25.0	0.78	3,000 pcs.	Yellow (YE)	553-60035
TLFX190DS-1x50WH	19.0	9.5	50.0	0.78	1,500 pcs.	White (WH)	553-60006
TLFX190DS-1x50YE	19.0	9.5	50.0	0.78	1,500 pcs.	Yellow (YE)	553-60016
TLFX254DS-2x25WH	25.4	12.7	25.0	0.93	2,000 pcs.	White (WH)	553-60027
TLFX254DS-2x25YE	25.4	12.7	25.0	0.93	2,000 pcs.	Yellow (YE)	553-60036
TLFX254DS-1x50WH	25.4	12.7	50.0	0.93	1,000 pcs.	White (WH)	553-60007
TLFX254DS-1x50YE	25.4	12.7	50.0	0.93	1,000 pcs.	Yellow (YE)	553-60017
TLFX381DS-2x25WH	38.1	19.1	25.0	0.98	1,000 pcs.	White (WH)	553-60028
TLFX381DS-2x25YE	38.1	19.1	25.0	0.98	1,000 pcs.	Yellow (YE)	553-60037
TLFX381DS-1x50WH	38.1	19.1	50.0	0.98	500 pcs.	White (WH)	553-60008
TLFX381DS-1x50YE	38.1	19.1	50.0	0.98	500 pcs.	Yellow (YE)	553-60018

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.

EN 45545-2

ASTM

NF F

UNI CEI

For product specific approvals and specifications please refer to the Appendix.