

Shrinkable markers "Ladder Style", thermal transfer

THTT DS - 2:1 Aerospace High Temperature

THTT is a 2:1 high temperature, flame retardant heat shrink marker. The material is pre-cut and formatted into a convenient "ladder" system that allows printing on both sides of the marker.

The printed marker is ideal for use in applications where high temperature and exposure to aggressive solutions are found. The pre-cut format not only allows printing on both sides of the marker but the user can also easily choose and pick each required marker. The tubing has been especially prepared so that the print performance is excellent at all times using HellermannTyton's printer range.

The material is also especially formulated to be printable with laser beam printers.

Features and benefits


- Shrink ratio 2:1
- PVDFX high temperature marker
- Thermal transfer or laser beam printable
- 50 mm and 25 mm pre-cut marker options as standard, other lengths available on request
- Available in black and white as standard
- Good mechanical strength and highly flexible
- Delivery in convenient storage boxes



THTT DS - High temperature heatshrink printable marker.

MATERIAL	Polyvinylidene Fluoride cross-linked (PVDFX)
Operating Temperature	-55 °C to +225 °C
Min. Shrink Temperature	+120 °C
Shrink Ratio	2:1
Recommended Ribbon Type	TTRHT
Thermal Transfer Printer	TT430, TT4030, TRAKMARK DS

RoHS ✓



For size matrix please refer to page 475.

TYPE	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Pack Cont.	Colour	Article-No.
THTT24DS-2X25BK	2.4	1.2	25.0	0.41	2,000 pcs.	Black (BK)	553-72519
THTT24DS-2X25WH	2.4	1.2	25.0	0.41	2,000 pcs.	White (WH)	553-72501
THTT24DS-1X50BK	2.4	1.2	50.0	0.41	1,000 pcs.	Black (BK)	553-72518
THTT24DS-1X50WH	2.4	1.2	50.0	0.41	1,000 pcs.	White (WH)	553-72500
THTT32DS-2X25BK	3.2	1.6	25.0	0.27	2,000 pcs.	Black (BK)	553-72521
THTT32DS-2X25WH	3.2	1.6	25.0	0.27	2,000 pcs.	White (WH)	553-72503
THTT32DS-1X50BK	3.2	1.6	50.0	0.27	1,000 pcs.	Black (BK)	553-72520
THTT32DS-1X50WH	3.2	1.6	50.0	0.27	1,000 pcs.	White (WH)	553-72502

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.