

Stainless steel ties with RFID transponder

MBTRFID – High Frequency (HF) and Ultra High Frequency (UHF)

Stainless steel RFID cable ties are fitted with a slide-on carrier for a high frequency (HF) or an ultra-high frequency (UHF) RFID transponder. These ties are ideal for product identification in all areas of harsh environment where high tensile strength and durability is of importance. The ties are especially suited for securing, serialisation, tracking and identification of products in the areas of resource management, electrical inspection, inventory, distribution and rental services as well as for easy management of maintenance and repair routines.


Features and benefits

- MBT stainless steel (316) tie complete with RFID transponder
- Especially suited for applications in harsh environments
- Patented non-releasable locking feature
- Flexible, contactless data communication
- Clear identification of objects through unique numbering
- Faster data management compared to paper solution
- More accurate documentation processes – prevention of human errors
- High frequency (HF – 13.56 MHz)
- Ultra high frequency (UHF – 869 MHz)
- Rewritable
- Standard colour red, black coating is also available as a special



MBTRFID – Stainless steel RFID cable ties for product identification in harsh environments.

MATERIAL	Stainless Steel (SS316), Polyester (SP)	
Frequency	13.56 MHz (HF)	869 MHz (UHF)
Idle Temperature	-25 °C to +70 °C	-40 °C to +85 °C
Operating Temperature	-25 °C to +70 °C	-40 °C to +85 °C
Flammability	non-burning (except coating)	




MBTRFID

TYPE	Frequency	Bundle Ø min.	Bundle Ø max.	Width (W)	Length (L)	N	Colour	Pack Cont.	Tools	Article-No.
MBT8HFCRFID	13.56 MHz (HF)	12.0	17.0	7.9	201.0	1,020	Red (RD)	50 pcs.	15-18;53	156-01167
MBT14HFCRFID	13.56 MHz (HF)	17.0	102.0	7.9	362.0	1,020	Red (RD)	50 pcs.	15-18;53	111-01586
MBT20HFCRFID	13.56 MHz (HF)	17.0	152.0	7.9	521.0	1,020	Red (RD)	50 pcs.	15-18;53	111-01587
MBT27HFCRFID	13.56 MHz (HF)	17.0	203.0	7.9	681.0	1,020	Red (RD)	50 pcs.	15-18;53	111-01588
MBT33HFCRFID	13.56 MHz (HF)	17.0	254.0	7.9	838.0	1,020	Red (RD)	50 pcs.	15-18;53	111-01589
MBT8HHFRFID	869 MHz (UHF)	12.0	17.0	7.9	201.0	1,020	Red (RD)	50 pcs.	15-18;53	156-01565
MBT14HHFRFID	869 MHz (UHF)	12.0	102.0	7.9	362.0	1,020	Red (RD)	50 pcs.	15-18;53	156-01566
MBT20HHFRFID	869 MHz (UHF)	12.0	152.0	7.9	521.0	1,020	Red (RD)	50 pcs.	15-18;53	156-01567
MBT27HHFRFID	869 MHz (UHF)	12.0	203.0	7.9	681.0	1,020	Red (RD)	50 pcs.	15-18;53	156-01568
MBT33HHFRFID	869 MHz (UHF)	12.0	254.0	7.9	838.0	1,020	Red (RD)	50 pcs.	15-18;53	156-01569

All dimensions in mm. Subject to technical changes.

Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

 = Minimum Loop Tensile Strength for Cable Ties (Newton)

Recommended Tools					
	15	16	17	18	53
	MK9SST	MK9PSST	HDT16	KST-STG200	RFID-HS9BT-HF
	604	604	605	605	558

For more information on toolings please refer to the Application Tooling chapter.