



Thermal transfer printer

TT4030

HellermannTyton's premium printer TT4030 is specifically designed for medium and heavy duty industrial applications. The 300 dpi print head fulfils all standard requirements for printing bar codes, warning signs, logos and written information. Optional premium quality accessories such as a perforator and cutter are designed to work seamlessly with the printer and will suit the most demanding needs.

Printing high definition graphics such as 2d barcodes, standard bar codes, numbers and text on adhesive labels, thermo plastics such as heat shrink and cable markers (Tiptags) is easily done.

A colour LCD Touchscreen with modern user interface helps intuitive operation.

Creation of professional looking industrial identification is simplified by the use of HellermannTyton's label creation software TagPrint Pro 3.0.

Whether in stand-alone mode, as a PC application or in a network - the robust TT4030 printers can meet every requirement.

Features and benefits

- High volume single sided printing
- Print on HellermannTyton heatshrink tubing, cable markers and labels
- Uses standard 300 m ribbons
- Barcodes: standard and 2D
- Print speed up to 300 mm/s (30 mm/s recommended for ladder style products and tubing)
- Multiple language selection
- Windows drivers: 32 / 64 bit for Windows XP, Windows Vista, Windows 7 and Windows 8



TT4030 thermal transfer printer for high volumes.

Print Method	Thermal transfer
Print Head Type	300 dpi, flat type
Print Speed	up to 300mm/s
Max. Print Width	105.70 mm
Label Height Max (metric)	2,000 mm
Interfaces	RS232 C, USB 2.0, Ethernet 10/100 Base T
Supported Barcodes, Printer	Standard, 2D
Printer Memory	256 MB RAM
Dimensions W x H x D	252 mm x 288 mm x 460 mm
Weight	10 kg



TYPE	Article-No.
TT4030	556-04037

Subject to technical changes.

TYPE	Description	Article-No.
P4030 Perforator	Perforator for TT4030	556-04051
Printer Roller for TT4030	Printer Roller for TT4030	556-04053
Printhead for TT4030	Printhead for TT4030	556-04052
S4030 Cutter	S4030 Cutter for TT4030	556-04050
TT External Reel Holder	External Reel Holder	556-00451

Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.