



## Thermal transfer printer

### TrakMark DS, Double Sided

The TrakMark DS is a high-performance printer for double-sided printing. This printer is perfect for double-sided printing on HellermannTyton shrinkable tubing. With two print heads mounted one on top of the other, the TrakMark DS prints onto both sides of the material at the same time. High reliability and multiple peripherals enable applications and solutions tailored to specific customer requirements. It is easy to use thanks to its display and clear status messages which can be shown in multiple languages. 300 dpi resolution ensures that barcodes, warning symbols, logos and text are as sharp as they can be.

#### Features and benefits

- High volume double sided printing
- Prints perfectly on HellermannTyton heatshrink ladder style products
- Uses standard 300 m ribbons
- Barcodes: standard and 2D
- Print speed up to 125 mm/s (30 mm/s recommended for ladder style products and tubing)
- Multiple language selection
- Windows drivers: 32/64 bit for Windows XP, Windows Vista, Windows 7 and Windows 8



One Step to the Web!



TrakMark DS printer.

<b>Print Method</b>	Thermal Transfer
<b>Print Head Type</b>	300 dpi, flat type
<b>Print Speed</b>	30, 40, 50, 75, 100, 125 mm/s
<b>Max. Print Width</b>	105.6 mm
<b>Label Height Max (metric)</b>	2,000 mm
<b>Interfaces</b>	RS232 C, USB 2.0, Ethernet 10/100 Base T
<b>Supported Barcodes, Printer</b>	Standard, 2D
<b>Printer Memory</b>	64 MB RAM
<b>Dimensions W x H x D</b>	248 mm x 395 mm x 554 mm
<b>Weight</b>	21 kg

RoHS

TYPE	Article-No.
TRAKMARK DS	556-05000

Subject to technical changes.

TYPE	Description	Article-No.
<b>S4000 Cutter</b>	S4000 Cutter for TT4000+ and TrakMark DS	556-04025
<b>P4000 Perforator</b>	Perforator for TT4000+ and TrakMark DS	556-04024
<b>TT External Reel Holder</b>	External Reel Holder	556-00451

Subject to technical changes.



For product specific approvals and specifications please refer to the Appendix.