




Thermal transfer ribbons for

Adhesive Labels


The thermal transfer print technology is based on heating up certain dots in the print head. This transfers the ink very precisely from the ribbon onto the surface of the printed material. All HellermannTyton ribbons consist of a special resin composition to maximise print performance. In combination with HellermannTyton printers the ribbons ensure the highest of print quality on all HellermannTyton thermal printable identification materials.

Features and benefits

- Thermal transfer ribbons for highest quality and performance of printed labels
- Ribbons are specifically designed to maximise print performance for the recommended material



Ribbons for printing on Adhesive Labels.



ID: The standard inside core diameter is 25.4 mm.

TYPE	Recommended Material	Colour	Width (W)	Reel Length	Article-No.
TT822OUT 60MM	323/823/880/892/951/1203/1204/1206/1208/1210/1211/1213/1216/1220/1221	Black (BK)	60.0	300 m	556-00111
TT822OUT 110MM	323/823/880/892/951/1203/1204/1206/1208/1210/1211/1213/1216/1220/1221	Black (BK)	110.0	300 m	556-00101
TT932DOUT 85MM	323/1209	Black (BK)	85.0	300 m	556-00117
TT932DOUT 110MM	323/1209	Black (BK)	110.0	300 m	556-00118
TT122OUT 60mm	1220/1221	Black (BK)	60.0	300 m	556-00060
TT122OUT 110mm	1220/1221	Black (BK)	110.0	300 m	556-00061
TTRR 110	Labels/1220/1221	Red (RD)	110.0	300 m	556-00208

All dimensions in mm. Subject to technical changes.

RoHS ✓