



Self-amalgamating Tapes – Medium Voltage Rubber Tape

HelaTape Power 700

Features and benefits

- Polyisobutylene-based self-amalgamating medium voltage tape
- Insulating and jacketing power cables up to 46 kV
- Provides electrical stability and permanent moisture sealing
- Perfect stretching properties allows fast and uniform application
- Excellent UV, moisture, corrosion and chemical resistance
- Temperature range from -40 °C to +90 °C
- Compatible with all extruded cable insulation materials



HelaTape Power 700 is a self-amalgamating medium voltage rubber tape.

MATERIAL	Polyisobutylene Rubber (PIBR)
Operating Temperature	-40 °C to +90 °C
Intermittent Operating Temperature	+90 °C
Water Absorption	0.02 %
Tensile Strength	2.4 N/mm ²
Elongation at break	700 %
Volume Resistance	10 ¹³ Ω cm
Dielectric Strength	35 kV/mm

HF ✓

RoHS ✓

TYPE	Thickness (T)	Width (W)	Length (L)	Colour	Article-No.
HTAPE-POWER700-PIB	0.50	19.0	10.0 m	Black (BK)	711-00308

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.