

Printed circuit board labels (ESD), thermal transfer Helatag 823 (White), PCB labelling

Helatag 823 labels have been designed to fit all areas when it comes to marking components on PCBs. The specially formulated adhesive labels give the highest quality print clarity when printed on thermal transfer printers. Designing and printing labels is simple and users can quickly print out professional labels in a matter of moments when using TagPrint Pro labelling software.

Features and benefits

- Labels for printed circuit boards
- Voltage rejecting adhesive properties
- · Permanent and durable identification
- For electrostatic sensitive applications

W

н



Secure identification of component parts and circuit boards with Helatag.

MATERIAL	Type 823, Polyester (PET), white (WH)		
Operating Temperature	-40 °C to +150 °C		
Curing Temperature	from +10 °C		
Adhesive	Acrylic		
Thickness of Foil	51 µm		
Chem. Material Properties	Excellent resistance against alcohol, petrol, solvents, butanol, ethyl- and butylcellosolve solvents, battery acid		
Recommended Ribbon Type	TT822OUT		
Thermal Transfer Printer	TT430, TT4030		





ТҮРЕ	Width (W)	Height (H)	Width of Liner (WL)	Labels per Row	Pack Cont.	Colour	Article-No.
TAG16TD3-823-WH	22.9	6.4	80.0	3 pcs.	10,000 pcs.	White (WH)	596-16823
TAG61TD3-823-WH	25.4	4.8	89.0	3 pcs.	10,000 pcs.	White (WH)	596-61823
TAG29TD3-823-WH	25.4	6.4	89.0	3 pcs.	7,500 pcs.	White (WH)	596-29823
TAG34TD3-823-WH	25.4	9.5	85.1	3 pcs.	7,500 pcs.	White (WH)	596-34823
TAG35TD3-823-WH	31.8	9.5	101.6	3 pcs.	7,500 pcs.	White (WH)	596-35823
TAG17TD2-823-WH	38.1	6.4	85.1	2 pcs.	5,000 pcs.	White (WH)	596-17823

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content. Other packaging options may also be available.

